

**IN THE UNITED STATES DISTRICT COURT  
FOR THE SOUTHERN DISTRICT OF NEW YORK**

\_\_\_\_\_  
**LEIGHTON TECHNOLOGIES LLC,**

**Plaintiff,**

**v.**


**OBERTHUR CARD SYSTEMS, S.A.,  
OBERTHUR CARD SYSTEMS OF  
AMERICA CORPORATION,**

**Defendants.**  
\_\_\_\_\_

)  
)  
) **Case No. 04-cv-02496**  
) **(CM)(LMS)**  
)

) **SECOND AMENDED COMPLAINT**  
)

) **DEMAND FOR JURY TRIAL**  
)  
)  
)



Plaintiff Leighton Technologies LLC (“Leighton Technologies”) by its attorneys, Sutherland Asbill & Brennan LLP, brings this patent infringement action against Defendants Oberthur Card Systems, S.A. (“OCS-France”) and Oberthur Card Systems of America Corporation (“OCS-America”) (collectively “Defendants”) and for its complaint hereby states and alleges as follows:

**JURISDICTION AND VENUE**

1. This Court has subject matter jurisdiction over this action pursuant to 28 U.S.C. §§ 1331 and 1338(a) because it arises under the patent laws of the United States.

2. This Court has personal jurisdiction over Defendants pursuant to N.Y. C.P.L.R. §§ 301 and 302(a)(1)-(3) (McKinney 2001) by virtue of Defendants’ transacting and soliciting business in this district. Upon information and belief, Defendants have had substantial and continuous contacts with this district by, among other things, engaging in activities that have placed infringing products into the stream of commerce in this district. Such activities by Defendants have injured Plaintiff Leighton Technologies.

3. Venue is proper in this district pursuant to 28 U.S.C. §§ 1391 (b)-(d) because a substantial part of the events giving rise to the claims occurred in this district and because OCS-France is an alien corporation.

### **THE PARTIES**

4. Plaintiff Leighton Technologies is a limited liability company organized and existing under the laws of the State of New York with its principal place of business at 75 Montebello Park, Suffern, NY 10901-3740. Leighton Technologies is the owner of several patents covering “smart cards” and processes for making “smart cards.” Smart cards are plastic cards with a silicon chip embedded into the body of the plastic that are used, *inter alia*, to enable secure financial payments and access secure locations.

5. Defendant OCS-France is a corporation organized and existing under the laws of France with its principal place of business at 71/73 rue des Hautes-Patures, 92726 Nanterre Cedex, France. Defendant OCS-France is a global manufacturer and distributor of smart cards.

6. Upon information and belief, Defendant OCS-America is a Delaware corporation having its principal place of business at 3150 E. Ana Street, Rancho Dominguez, CA 90221.

### **THE FOUR PATENTS-IN-SUIT**

7. Each of the four patents-in-suit covers processes for making certain types of smart cards. One of the four patents-in-suit also covers smart cards made in accordance with one of the processes.

8. United States Patent No. 5,817,207 (the “207 patent”), entitled “Radio Frequency Identification Card And Hot Lamination Process For The Manufacture Of Radio Frequency Identification Cards,” was duly and lawfully issued on October 6, 1998, based upon an

application filed by the inventor, Keith R. Leighton. A copy of the '207 patent is attached hereto as Exhibit A.

9. United States Patent No. 6,036,099 (the "'099 patent"), entitled "Hot Lamination Process For The Manufacture Of A Combination Contact/Contactless Smart Card And Product Resulting Therefrom," was duly and lawfully issued on March 14, 2000, based upon an application filed by the inventor, Keith R. Leighton. A copy of the '099 patent is attached hereto as Exhibit B.

10. United States Patent No. 6,214,155 B1 (the "'155 patent"), entitled "Radio Frequency Identification Card And Hot Lamination Process For The Manufacture Of Radio Frequency Identification Cards," was duly and lawfully issued on April 10, 2001, based upon an application filed by the inventor, Keith R. Leighton. A copy of the '155 patent is attached hereto as Exhibit C.

11. United States Patent No. 6,514,367 B1 (the "'367 patent"), entitled "Hot Lamination Process For The Manufacture Of A Combination Contact/Contactless Smart Card," was duly and lawfully issued on February 4, 2003, based upon an application filed by the inventor, Keith R. Leighton. A copy of the '367 patent is attached hereto as Exhibit D.

12. Leighton Technologies is the owner by assignment of the '207, '099, '155, and '367 patents (collectively, "the Patents") and has the right to sue, and recover damages, for infringement thereof.

### **GENERAL ALLEGATIONS**

13. Upon information and belief, from at least early 1999, OCS-France made smart cards in France according to a manufacturing process (the "OCS-France Manufacturing

Process”). Upon information and belief, these smart cards were imported into, and sold and used in, New York and other places throughout the United States.

14. Upon information and belief, since early 1999, OCS-France has exercised direct and substantial control over certain of its U.S. Affiliates that make and sell smart cards (“U.S. Affiliates”).

15. Upon information and belief, OCS-France’s U.S. Affiliates include but are not limited to OCS-America.

16. Upon information and belief, since early 1999, OCS-France has provided and continues to provide its U.S. Affiliates with the technological details of, and support for, the OCS-France Manufacturing Process or other process.

17. Upon information and belief, since early 1999, OCS-France has actively directed, caused, and encouraged its U.S. Affiliates to make smart cards in the United States in accordance with the OCS-France Manufacturing Process or other process, to sell such smart cards in New York and other places throughout the United States, and to cause such smart cards to be used in New York and other places throughout the United States.

18. Upon information and belief, OCS-America has made smart cards in the United States in accordance with the OCS-France Manufacturing Process or other process, sold and offered to sell such smart cards in New York and other places throughout the United States, and used or caused such smart cards to be used in New York and other places throughout the United States.

19. Upon information and belief, Defendants have engaged in and continue to engage in continuous and substantial activity in New York.

20. Upon information and belief, Defendants have committed and continue to commit tortious acts inside and outside of New York, and these acts have caused and continue to cause direct injury to Leighton Technologies.

21. Upon information and belief, Defendants regularly transact and solicit business in New York, engage in other persistent courses of conduct in New York, and derive substantial revenue from goods used or consumed, or services rendered, in New York.

22. By virtue of its aforementioned acts, Defendants, upon information and belief, expect to or should reasonably expect such acts to have consequences in New York, and Defendants derive substantial revenue from interstate and international commerce.

### **COUNT I**

#### **(PATENT INFRINGEMENT)**

23. Leighton Technologies repeats and incorporates the allegations contained in paragraphs 1 through 22 above as is set forth fully herein.

24. Upon information and belief, OCS-France has imported into the United States certain smart cards that were made in France pursuant to the OCS-France Manufacturing Process and, thus, in accordance with the Patents. This importation has infringed the Patents under 35 U.S.C. § 271.

25. Upon information and belief, OCS-France has induced infringement of and is continuing to induce infringement of the Patents by providing its U.S. Affiliates with technological details of, and support for, the OCS-France Manufacturing Process and by actively directing, causing, and encouraging its U.S. Affiliates to make smart cards in the United States in accordance with the OCS-France Manufacturing Process, which smart cards were sold and used

in New York and other places throughout the United States. This inducement is an infringement of the Patents under 35 U.S.C. § 271(b), since the use of the OCS-France Manufacturing Process by OCS-France's U.S. Affiliates, and the sale, offer for sale, and use of smart cards made in accordance therewith, is a direct infringement of the Patents under 35 U.S.C. § 271(a).

26. Upon information and belief, OCS-France through its actions and the U.S. Affiliates through their actions have contributed to the infringement of and are continuing to contribute to the infringement of the Patents.

27. Upon information and belief, OCS-America has and is infringing, or inducing the infringement of, or contributing to the infringement of the claims of the Patents in violation of 35 U.S.C. § 271 by, among other things, making, using, selling and/or offering to sell the inventions claimed in the Patents and products made by the processes claimed in the Patents.

28. Defendants have committed the foregoing infringing activities without license from Leighton Technologies.

29. Upon information and belief, Defendants knew the Patents existed before committing the foregoing infringing acts, thereby willfully and deliberately infringing the Patents. This action is "exceptional" within the meaning of 35 U.S.C. § 285, and Leighton Technologies therefore is entitled to its reasonable attorneys' fees and litigation expenses. Additionally, Leighton Technologies' damages should be trebled pursuant to 35 U.S.C. § 284 because of Defendants' willful infringement of the Patents.

30. As a direct and proximate result of Defendants' infringing conduct and the threat of continuing infringement, Leighton Technologies has suffered and will continue to suffer irreparable harm and damages for which Leighton Technologies has no adequate remedy at law.

31. Unless this Court enjoins Defendants, Defendants will continue to infringe the Patents.

32. If Leighton Technologies is unable to stop Defendants' patent infringement, Leighton Technologies will suffer irreparable harm. Leighton Technologies' remedy at law is inadequate to compensate it for the injuries already inflicted and further threatened by Defendants. Therefore, Defendants should be enjoined pursuant to 35 U.S.C. § 283.

**PRAYER FOR RELIEF**

WHEREFORE, Plaintiff prays for judgment against Defendants as follows:

A. Permanently enjoining Defendants – together with each of its affiliates, subsidiaries, officers, agents, servants, employees, and attorneys, and all persons in active concert or participation with any of them who receive actual notice of this Court's order by personal service or otherwise from infringing the Patents in any manner.

B. Requiring Defendants to file and serve on Leighton Technologies, within 30 days after service of an injunction, a written report under oath setting forth in detail Defendants' compliance with the injunction.

C. For a judicial determination and declaration that OCS-France has infringed the Patents.

D. For a judicial determination and declaration that OCS-France's inducement of its U.S. Affiliates to infringe the Patents by providing said affiliates with technological details of, and support for, the OCS-France Manufacturing Process – and by actively directing, causing, and encouraging these affiliates to make and sell smart cards in the United States in accordance with the OCS-France Manufacturing Process – infringes the Patents.

E. For a judicial determination and declaration that OCS-France contributes or has contributed to the infringement of the Patents.

F. For a judicial determination and declaration that OCS-America infringes or has infringed the Patents either directly or indirectly or by inducement or contributing to infringement.

G. For a judicial determination and declaration that because Defendants' infringement of the Patents is willful and deliberate, this is an exceptional case under 35 U.S.C. § 285.

H. For an order requiring Defendants to account for the sales and profits related to the sale of smart cards made using its infringing process.

I. For an award, to be determined at trial, of damages adequate to compensate Leighton Technologies for Defendants' infringement and Leighton Technologies' costs, but in no event less than a reasonable royalty – plus pre-judgment and post-judgment interest – and for such damages to be trebled, pursuant to 35 U.S.C. § 284.

J. For an award of Leighton Technologies' reasonable attorneys' fees and expenses, pursuant to 35 U.S.C. § 285.


K. For such other and further relief as this Court may deem just and proper.

#### **DEMAND FOR JURY TRIAL**

Pursuant to Federal Rule of Civil Procedure 38(b), Plaintiff Leighton Technologies LLC hereby demands a jury trial on all triable issues raised in this action.



Date: October 25, 2005

A handwritten signature in black ink, appearing to read "Robert A. Gutkin", written over a horizontal line.

Robert A. Gutkin, Esq. (Pro hac vice)  
Blair M. Jacobs, Esq. (Pro hac vice)  
Christina A. Ondrick, Esq. (Pro hac vice)  
SUTHERLAND ASBILL & BRENNAN LLP  
1275 Pennsylvania Avenue, N.W.  
Washington, DC 20004-2415  
Tel: 202-383-0751  
Fax: 202-637-3593

*Attorneys for Plaintiff*  
LEIGHTON TECHNOLOGIES LLC

## Exhibit A



US005817207A

# United States Patent [19]

Leighton

[11] Patent Number: 5,817,207

[45] Date of Patent: Oct. 6, 1998

[54] RADIO FREQUENCY IDENTIFICATION CARD AND HOT LAMINATION PROCESS FOR THE MANUFACTURE OF RADIO FREQUENCY IDENTIFICATION CARDS

[76] Inventor: Keith R. Leighton, 2817 Fulmer Rd., Lorain, Ohio 44053

[21] Appl. No.: 727,789

[22] Filed: Oct. 7, 1996

## Related U.S. Application Data

[60] Provisional application No. 60/005,685 Oct. 17, 1995.

[51] Int. Cl.<sup>6</sup> B32B 31/20

[52] U.S. Cl. 156/298; 156/312

[58] Field of Search 156/300, 312, 156/311, 298

## References Cited

### U.S. PATENT DOCUMENTS

4,450,024 5/1984 Haghir-Tehrani et al. 156/108  
4,701,236 10/1987 Vieilledent  
4,792,843 12/1988 Haghir-Tehrani et al.  
4,795,898 1/1989 Bernstein et al.  
4,980,802 12/1990 Champagne et al.  
5,067,008 11/1991 Yanaka et al. 357/81

5,097,117 3/1992 Champagne et al.  
5,173,840 12/1992 Kodai et al.  
5,208,450 5/1993 Uenishi et al.  
5,268,699 12/1993 Laute et al.  
5,396,650 3/1995 Terauchi 455/38.2  
5,412,192 5/1995 Hoss  
5,438,750 8/1995 Venambre  
5,567,362 10/1996 Grun


Primary Examiner—Francis J. Lorin

Attorney, Agent, or Firm—Oldham & Oldham Co., L.P.A.

## [57] ABSTRACT

A plastic card, such as a radio frequency identification card, including at least one electronic element embedded therein and a hot lamination process for the manufacture of radio frequency identification cards and other plastic cards including a micro-chip embedded therein. The process results in a card having an overall thickness in the range of 0.028 inches to 0.032 inches with a surface suitable for receiving dye sublimation printing—the variation in card thickness across the surface is less than 0.0005 inches. A card manufactured in accordance with the present invention also complies with all industry standards and specifications. Also, the hot lamination process of the present invention results in an aesthetically pleasing card. The invention also relates to a plastic card formed in accordance with the hot lamination process of the present invention.

17 Claims, 3 Drawing Sheets








U.S. Patent

Oct. 6, 1998

Sheet 1 of 3

5,817,207



U.S. Patent

Oct. 6, 1998

Sheet 2 of 3

5,817,207




FIG. - 4




FIG. - 5




FIG. - 6







FIG. - 7

U.S. Patent

Oct. 6, 1998

Sheet 3 of 3

5,817,207



5,817,207

1

# RADIO FREQUENCY IDENTIFICATION CARD AND HOT LAMINATION PROCESS FOR THE MANUFACTURE OF RADIO FREQUENCY IDENTIFICATION CARDS

This application claims the benefit of the following: U.S. Provisional Application No.: 60/005,685, filing date Oct. 17, 1995.

## FIELD OF THE INVENTION

The present invention relates generally to plastic cards and the manufacture thereof, and more particularly to radio frequency identification (RFID) cards and the manufacture of RFID cards that conform to industry size and performance standards and conventions and that have a superior outer surface to known RFID cards such that card may receive dye sublimation printing or the like.

## BACKGROUND OF THE INVENTION

As the use of plastic cards for credit cards, automated teller machine (ATM) cards, identification cards, and like continues to become more widespread, the problems associated with the use of such cards correspondingly increase. Credit card fraud and identification card fraud are becoming larger problems everyday, and this fraud has introduced uncertainties into our systems of commerce and our security systems. Using easily available technology, criminals are able to manufacture credit/debit cards, ATM cards, identification cards, and the like having another's account code, identification code, or other personal information embedded in the magnetic stripe thereof. Thus, for example, criminals may steal hundreds or thousands of legitimate credit card account numbers and manufacture many additional cards bearing the stolen information. These fraudulent cards are then usable by the criminals to purchase goods and to receive cash with the legitimate card holder and the card issuer left holding the bill. Likewise, so called debit cards are becoming increasingly popular. These cards have stored thereon a certain amount of value for which the card owner has previously paid. For example, a subway rider may purchase a card good for 50 fares, with one fare being deducted from the card each time the owner rides the subway. Criminals have also been able to manipulate the data stored on these cards to defraud the merchants and others.

The ease in which criminals have been able to manufacture and/or manipulate known cards results from the existence of the easily altered magnetic stripe storage medium used by known cards. These magnetic stripes are easily programmed and reprogrammed using commonly available technology. Thus, there has been found a need in the plastic card industry to provide a more secure plastic card that is very difficult or impossible to fraudulently manipulate. The most likely solution to the above-noted problems associated with known plastic cards is the RFID card and other cards including computer chips embedded therein rather than, or in addition to, a magnetic stripe. While these RFID cards and like have been found to be successful in preventing or limiting fraud, they are more difficult and expensive to manufacture relative to ordinary magnetic stripe cards. One of the biggest obstacles to the wide spread manufacture and use of RFID cards has been the inability of card manufacturers to manufacture an RFID card that meets all industry standards and specifications, such as those set by the International Standards Organization (ISO), that are sufficiently aesthetically pleasing (wherein the embedded electronics are

2

hidden from view), and that have a sufficiently regular or flat surface such that one or both surfaces of the card may be printed on using the very popular and widespread dye sublimation technology. Known plastic cards with computer chips and like embedded therein are too thick to work in connection with existing card reading machinery (ATM machines, telephones, and like) and have a surface that is too irregular to properly and consistently receive dye sublimation printing. Furthermore, prior attempts to manufacture a sufficiently thin plastic card including a computer chip embedded therein have resulted in a card with inferior aesthetic qualities such as the ability to see the embedded computer chip through the plastic.

## SUMMARY OF THE INVENTION

The present invention is therefore directed to a plastic card having at least one electronic element embedded therein and to a hot lamination method for the manufacture of plastic cards including at least one electronic element therein. The card has an overall thickness in the range of 0.028 inches to 0.032 inches and comprises a plastic core having at least one electronic element embedded therein with at least one of the upper and lower surfaces of the core comprising a coating printed or otherwise applied thereon. An overlamine film is preferably provided over the coated surface of the core and the resulting card has a variation in thickness across the surfaces thereof of no greater than approximately 0.0005 inches. The hot lamination method of the present invention comprises the steps of providing first and second plastic core sheets, positioning at least one electronic element between the first and second core sheets to thus form a core, and placing the core in a laminator and closing the laminator without applying laminator ram pressure to the core. A heat cycle is applied to the core sheets in the laminator thus liquefying or partially liquefying the sheets. The laminator ram pressure is then increased in combination with the heat. A cooling cycle is then applied to the core in the laminator, preferably with an associated increase in ram pressure, and the core is removed from the laminator. At least one surface of the core is then printed on using a printing press or similar printing apparatus, a sheet of overlamine film is placed on at least one side of the core, and the core is then again placed in a laminator. A heat cycle is applied to the core with its overlamine film, and a cooling cycle is thereafter applied, resulting in a sheet of plastic card stock from which one or more cards may be cut. The invention is also directed to a card manufactured in accordance with the above process which results in a plastic card having a thickness in the range of approximately 0.028 inches to 0.032 inches with a surface smoothness of at least approximately 0.0005 inches as is required by ISO and American National Standards Institute (ANSI) standards.

The present invention provides numerous advantages over known plastic cards and known plastic card manufacturing processes, including the formation of a plastic card with electronic elements such as a computer chip embedded therein with a pleasing aesthetic appearance, with a sufficiently smooth and regular surface such that the card may receive dye sublimation printing, and with sufficient durability and characteristics to comply with all industry specifications and standards.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a top plan view of a plastic card in accordance with the present invention;

FIG. 2 is a side elevational view of the card shown in FIG. 1;



5,817,207

3

FIGS. 3A-3C are top plan views of various electronic elements that may be embedded in a card in accordance with the present invention;

FIG. 4 is an exploded, schematic view of an electronic element position between two plastic core sheets to form a core;

FIG. 5 is a top plan view of a plurality of electronic elements positioned on a sheet of plastic core stock such that they may be covered by a similar sheet of core stock;

FIG. 6 is a schematic cross-sectional view of one or more electronic elements positioned between sheets of plastic core stock;

FIG. 7 schematically illustrates a book comprising the core, as it is positioned in a laminator apparatus;

FIG. 8 schematically illustrates the core as it is being printed on after removal from the laminator using a printing press or similar printing apparatus;

FIG. 9 is a cross-sectional view schematically illustrating the application of an overlamine film to at least one side of the core;

FIG. 10 schematically illustrates the core with overlamine film, as it is placed in a laminator for final processing to form a sheet of card stock.

#### DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to a plastic card including at least one electronic element embedded therein. The present invention also relates to a hot lamination process for the manufacture of plastic cards, and more particularly to a hot lamination process for the manufacture of plastic cards that include an electronic element, such as a computer chip or other electronic element embedded therein. The electronic element may perform a wide variety of functions and take a wide variety of forms. Such cards, without regard to the particular electronic element embedded therein, will hereinafter be referred to as radio frequency identification (RFID) cards. The present invention also relates to a card formed in accordance with the invention.

Referring now to FIG. 1, there can be seen a plastic RFID card 10 manufactured in accordance with the present invention and including an electronic element 20 embedded therein. Card 10 includes an upper surface 12 and a lower surface 14. Electronic element 20 may take a wide variety of forms and perform a wide variety of functions. As shown in FIG. 3A-3C respectively, electronic element 20, 20', 20" may be provided by a micro-chip 22 including a wire antenna 24 connected thereto, a micro-chip 22' and a circuit board antenna 24', a read/write micro-chip 22" and a wire coil antenna 24", or any other suitable electronic element. These electronic elements 20, 20', 20" and their insertion into plastic cards is not new, however, the present invention provides a new hot lamination process for manufacturing plastic cards 10 with these electronic elements 20, 20', 20" embedded therein such that the cards 10 are of a superior quality, such that the cards 10 meet all ISO and other industry specifications and standards, in such that at least one of the upper and lower surfaces 12, 14 of card 10 is sufficiently smooth and is otherwise is capable of receiving dye sublimation printing. Specifically, a card in accordance with the present invention has a thickness of approximately in the range of 0.028 inches to 0.032 inches with a surface smoothness of 0.0005 inches.

As shown in FIGS. 4-10 one or more cards 10 in accordance with the present invention may be manufactured

4

by positioning an electronic element 20 between first and second sheets of card stock 30, 32 to form a core 33. Preferably is shown in FIG. 5-10, a plurality of cards are manufactured simultaneously, in thus, a plurality of electronic elements 20 are positioned between the first and second sheets of plastic core stock 30, 32 (only the second sheet 32 begin shown in FIG. 5 for clarity). When a plurality of electronic elements 20 are positioned between first and second sheets plastic core stock 30, 32, electronic elements 20 are properly positioned relative to one another such that a plurality cards may be cut from the resulting card stock. Plastic core sheets 30, 32 may be provided by a wide variety of plastics, the preferred being polyvinyl chloride (PVC) having a thickness in the range of 0.007 inches to 0.024 inches and preferably having a thickness of approximately 0.0125 inches each. Those skilled in the art will recognize that the thickness of the plastic core sheets will depend upon the thickness of the one or more electronic elements that are to be embedded therebetween. Other suitable plastics that may be utilized include polyester, acrylonitrile-butadiene-styrene (ABS), and any other suitable plastic.

Subsequent to placing one or more electronic elements 20 between the first and second sheets 30, 32 of plastic core stock to form a core 33, this core 33 is placed in a laminator apparatus 40 of the type well known in the art of plastic card manufacturing. As is shown in FIG. 7, laminator 40 includes upper and lower platens 42, 44 for applying ram pressure to an article positioned therebetween. In addition to the ability to apply ram pressure, laminator 40 is preferably of the type having controlled platens 42, 44 that may provide both heat and chill cycles and preferably includes cycle timer to regulate cycle time. Core 33 is positioned between first and second laminating plates 50, 52, one of which is preferably matte finished to provide laminated core 33 with at least one textured outer surface. First and second laminating pads 60, 62 are positioned outside of the laminating plates 50, 52, and first and second steel plates 70, 72 are likewise positioned outside of pads 60, 62 and the entire assembly forms a book 35 for being positioned in laminator 40 between platens 42, 44.

Once book 35 is positioned in laminator 40 as shown in FIG. 7, the first lamination cycle is initiated by closing laminator platens 42, 44, preferably applying little or no ram pressure to book 35. A laminator heat cycle is initiated, bringing the temperature of platens 42, 44 up to a range of 275° F. to 400° F., and most preferably up to a range of 300° F. to 370° F. for a period of greater than 5 minutes, and preferably in the range of 7 to 10 minutes. Once the heat cycle has been applied to the book 35 as is set forth above, the ram pressure of laminator 40 is increased to facilitate the flow of the plastic core sheets 30, 32 so that the one or more electronic elements 20 are encapsulated there by, and so that sheets 30, 32 form a uniform core 33 (seen most clearly in FIGS. 8-10) with upper and lower surfaces 34, 35. As mentioned, the use of matte finished laminator plates 50, 52 provides surfaces 34, 35 with a slightly roughened or textured quality which will facilitate the application of a coating thereto as is discussed below. The ram pressure applied during the heat cycle and the length of the heat cycle may vary, depending especially upon the size of sheets 30, 32. For example, the cycle time may be in the range of 10-15 minutes. In one example, a ram pressure of 940.135 pounds per square inch (p.s.i.) was applied for 10-15 minutes to form a uniform core 33, using sheets 30, 32 of a size in the range of 12 inches by 24 inches to 24 inches by 36 inches.

Subsequent to the above heat cycle, laminator 40 applies a chill cycle to book 35 during which time the ram pressure



5,817,207

5

of the laminator 40 is increased, preferably by approximately 25% until the platens 42,44 have cooled to approximately 40° F. to 65° F. for approximately 10-15 minutes. Core 33 may then be removed from laminator 40 for additional processing.

Subsequent to the removal of core 33 from laminator 40, and as illustrated in FIG. 8, core 33 is coated on at least one of its upper and lower surfaces 34, 35 with a layer of printing ink 36. This may be accomplished using a wide variety of printing techniques such as offset printing, letterpress printing, screen printing, roller coating, spray printing, litho-printing, and other suitable printing techniques. As shown in FIG. 8, core 33 is fed in the direction indicated with arrow A through a printing press, a lithographic printer, or a similar apparatus 80. This printing step is performed to coat at least one surface 34, 35 of core 33 with a layer of aesthetically pleasing ink 36. This layer of ink 36 cosmetically hides the one or more electronic elements 20 that are embedded within core 33, and prevents these one or more electronic elements 20 from showing through the relatively thin core 33. In this manner, the one or more electronic elements 20 encapsulated in core 33 are completely hidden from view without requiring the plastic used in the manufacture of core 33 to be excessively thick.

Referring now to FIGS. 9-10, the final processing of core 33, which now comprises a layer of ink 36 or the like on at least one surface 34,35 thereof, is schematically illustrated. A layer of overlamine film such as clear overlamine film 38,39 is positioned on at least one ink coated surface 34,35 of core 33, and preferably core 33 is positioned between two similar sheets of overlamine film 38,39 as shown. Overlamine film is very thin, for example in the range of 0.0015" thick. A book 135 is then constructed for insertion into laminator 40 as is schematically illustrated FIG. 10. Book 135 comprising core 33, including at least one layer of ink 36 and at least one layer of overlamine film 38, 39 is positioned between laminating plates which are preferably highly polished plates such as mirror finished stainless steel plates 90, 92. Book 135 also comprises first and second laminating pads 60, 62 and first and second steel plates 70, 72 as is discussed above in relation to FIG. 7.

When book 135 is positioned between upper and lower platens 42,44 of laminator 40 as shown in FIG. 10, the laminator is closed and a heat cycle in the range of 175° F. to 300° F., and most preferably in the range of 180° F. to 275° F., is applied to book 135 for a period of 10 to 25 minutes with a ram pressure that varies depending upon sheet size or the ram size of the laminator 40, but which is typically approximately 1000 p.s.i. with an 18 inch diameter ram. The laminator 40 is then caused to execute a chill cycle, preferably with a corresponding increase in ram pressure. For example, the chill temperature may be in the range of 40° F. to 65° F. and last for a period of 10 to 25 minutes. A ram pressure increase of approximately 25% over the pressure used for the heat cycle has been found to be most preferable.

Subsequent to the above described second lamination cycle as illustrated in FIG. 10, a sheet of plastic card stock is provided which comprises at least core 33 with at least one surface 34,35 thereof covered by a layer of ink 36, and with at least one surface 34,35 thereof covered by a layer of overlamine film 38, 39. Preferably plastic card stock manufactured in accordance with the present invention comprises core 33 covered on both surfaces 34,35 with a layer of ink 36 which is positioned between layers of overlamine film 38,39, all of which has been laminated together as described. One or more cards 10 then may be cut

6

from the resulting plastic card stock and card 10 will have a thickness in the range of 0.028 inches to 0.032 inches with variation in overall thickness across the surfaces 12, 14 thereof being no greater than approximately 0.0005 inches. The one or more cards 10 can thus be said to have a surface smoothness of approximately 0.0005 inches or better. Thus, a card 10 manufactured in accordance with the present invention includes at least one surface 12,14 at preferably both surfaces 12,14 that are sufficiently smooth and regular to receive dye sublimation printing.

Those skilled in the art will recognize that the foregoing description has set forth the preferred embodiment of the invention in particular detail and it must be understood that numerous modifications, substitutions, and changes may be undertaken without departing from the true spirit and scope of the present invention as defined by the ensuing claims.

What is claimed is:

1. A process for incorporating at least one electronic element in the manufacture of a plastic card, comprising the steps of:

- (a) providing first and second plastic core sheets;
- (b) positioning said at least one electronic element in the absence of a non-electronic carrier directly between said first and second plastic core sheets to form a core, said plastic core sheets defining a pair of inner and outer surfaces of said core;
- (c) positioning said core in a laminator apparatus, and subjecting said core to a heat and pressure cycle, said heat and pressure cycle comprising the steps of:
  - (i) heating said core for a first period of time;
  - (ii) applying a first pressure to said core for a second period of time such that said at least one electronic element is encapsulated by said core;
  - (iii) cooling said core while applying a second pressure to said core;
- (d) coating at least one of said outer surfaces of said core with a layer of ink; and
- (e) applying a layer of overlamine film to at least one of said outer surfaces of said core.

2. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said laminator apparatus has first and second laminating plates, at least one of said first and second laminating plates having a matte finish for creating a textured surface on at least one of said outer surfaces of said core.

3. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 2, wherein each of said first and second laminating plates has a matte finish for creating said textured surface on both of said outer surfaces of said core.

4. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said first and second plastic core sheets are made from a material selected from the group consisting of polyvinyl chloride, polyester, and acrylonitrile-butadiene-styrene, each of said sheets having a thickness in the range of 0.007 to 0.024 inch.

5. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 4, wherein said first and second plastic core sheets have a thickness of approximately 0.0125 inch.

6. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said second pressure is greater than said first pressure.

5,817,207

7

7. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 6, wherein said second pressure is at least approximately 25% greater than said first pressure.

8. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said core is heated in step (c)(i) to a temperature in the range of 275° F. to 400° F. and said first period of time is at least five (5) minutes.

9. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said first pressure is approximately 1000 p.s.i. and said second period of time is at least 10 minutes.

10. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said step (d) is carried out utilizing a printing press.

11. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said step (d) is carried out utilizing a coating technique selected from the group consisting of silk screen printing, offset printing, letterpress printing, screen printing, roller coating, spray printing, and litho-printing.

12. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said step (e) of applying a layer of overlaminat film comprises the further steps of:

- (a) positioning an overlaminat film on at least one ink coated surface of said core;
- (b) subjecting said core to a second heat and pressure cycle comprising the steps of:
  - (i) heating said core to a temperature between approximately 175° F. to 300° F. for approximately 10 to 25 minutes;
  - (ii) applying approximately 1000 p.s.i. pressure to said core; and
  - (iii) cooling said core to a temperature in the range of approximately 40° F. to 65° F. for approximately 10 to 25 minutes.

13. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in

8

claim 1, wherein said at least one electronic element is a micro-chip and an associated wire antenna.

14. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said at least one electronic element is a micro-chip and an associated circuit board antenna.

15. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said at least one electronic element is a read/write integrated chip and an associated antenna.

16. A hot lamination process for the manufacture of plastic cards, said process comprising the steps of:

- (a) providing first and second plastic core sheets;
- (b) positioning at least one electronic element in the absence of a non-electronic carrier directly between said first and second plastic core sheets to form a layered core;
- (c) positioning said core in a laminator apparatus, and subjecting said core to a heat and pressure cycle, said heat and pressure cycle comprising the steps of:
  - (i) heating said core in said laminator, in the presence of a minimal first ram pressure, to a temperature which causes controlled flow of said plastic which makes up said first and second plastic core sheets;
  - (ii) applying a second pressure uniformly across said core for encapsulating said at least one electronic element within said controlled flow plastic;
  - (iii) subsequently cooling said core in conjunction with the concurrent application of a third pressure uniformly across said core, said core including and upper and lower surfaces;
- (d) printing on at least one of said upper and lower surfaces of said core such that a layer of ink is applied to at least a portion of said at least one upper and lower surface of said core.

17. The method as recited in claim 16 wherein said first and second core layers are devoid of any appreciable cut-outs.

\* \* \* \* \*

## Exhibit B



US006036099A

# United States Patent [19] Leighton

[11] Patent Number: 6,036,099  
[45] Date of Patent: Mar. 14, 2000

[54] HOT LAMINATION PROCESS FOR THE MANUFACTURE OF A COMBINATION CONTACT/CONTACTLESS SMART CARD AND PRODUCT RESULTING THEREFROM

[76] Inventor: Keith Leighton, 2817 Fulmer Rd., Lorain, Ohio 44053

[21] Appl. No.: 08/918,582

[22] Filed: Aug. 19, 1997

## Related U.S. Application Data

[63] Continuation-in-part of application No. 08/727,789, Oct. 7, 1996.

[51] Int. Cl.<sup>7</sup> ..... G06K 19/02; G06K 19/06; B32B 31/00; C09S 5/02

[52] U.S. Cl. .... 235/488; 235/492; 156/182; 156/154; 156/267; 156/311; 156/312

[58] Field of Search ..... 235/488, 492, 235/486, 375; 360/2; 156/182, 154, 267, 311, 312

## [56] References Cited

### U.S. PATENT DOCUMENTS

3,994,225	11/1976	Sitzberger	101/426
4,450,024	5/1984	Haghini-Tehrani et al.	156/108
4,701,236	10/1987	Vicilledent	
4,792,843	12/1988	Haghini-Tehrani et al.	
4,795,898	1/1989	Bernstein et al.	
4,841,134	6/1989	Hida et al.	235/488
4,980,802	12/1990	Champagne et al.	
5,067,008	11/1991	Yanaka et al.	357/81



5,097,117	3/1992	Champagne et al.	
5,173,840	12/1992	Kodai et al.	
5,208,450	5/1993	Uenishi et al.	235/492
5,268,699	12/1993	Laute et al.	
5,272,596	12/1993	Honore et al.	
5,396,650	3/1995	Terauchi	
5,412,192	5/1995	Hoes	
5,438,750	8/1995	Venambre	
5,567,362	10/1996	Grun	
5,809,633	9/1998	Mundigl et al.	29/600

Primary Examiner—Donald Hajec  
Assistant Examiner—Daniel Sherr  
Attorney, Agent, or Firm—Oldham & Oldham Co., L.P.A.

## [57] ABSTRACT

A plastic smart card, such as a card having a radio frequency identification (RFID) proximity function, including at least one electronic element embedded therein and a physical contact card function and the hot lamination process for the manufacture of this dual function smart card and other plastic cards including a micro-chip embedded therein. The process results in a card having a preferred overall thickness in the range of 0.028 inches to 0.032 inches with a surface suitable for receiving dye sublimation printing—the variation in card thickness across the surface should not exceed 0.0005 inches. A card manufactured in accordance with the present invention also complies with all industry standards and specifications. Also, the hot lamination process of the present invention results in an aesthetically pleasing card. The invention also relates to a plastic card formed in accordance with the hot lamination process of the present invention.

18 Claims, 4 Drawing Sheets





U.S. Patent

Mar. 14, 2000

Sheet 1 of 4

6,036,099



U.S. Patent

Mar. 14, 2000

Sheet 2 of 4

6,036,099

FIG.- 2A




FIG.- 3A




FIG.- 3B





FIG.- 4

U.S. Patent

Mar. 14, 2000

Sheet 3 of 4

6,036,099




FIG. - 5A





FIG. - 6





U.S. Patent

Mar. 14, 2000

Sheet 4 of 4

6,036,099





1

6,036,099

# HOT LAMINATION PROCESS FOR THE MANUFACTURE OF A COMBINATION CONTACT/CONTACTLESS SMART CARD AND PRODUCT RESULTING THEREFROM

This application is a continuation-in-part of copending application Ser. No. 08/727,789 filed Oct. 7, 1996.

## FIELD OF THE INVENTION

The present invention relates generally to plastic cards and the manufacture thereof by a hot lamination process, and more particularly to smart cards and the manufacture of these such that they conform to industry size and performance standards and conventions and that have a superior outer surface as compared to known smart cards such that the card may receive dye sublimation printing or the like. Even more specifically, the preferred embodiments of the present invention relate to dual function cards containing imbedded electronic elements as well as an exposed electronic contact surface.

## BACKGROUND OF THE INVENTION

As the use of plastic cards for credit cards, automated teller machine (ATM) cards, identification cards, and like continues to become more widespread, the problems associated with the use of such cards correspondingly increase. Credit card fraud and identification card fraud are becoming larger problems everyday, and this fraud has introduced uncertainties into our systems of commerce and our security systems. Using easily available technology, criminals are able to manufacture credit/debit cards, ATM cards, identification cards, and the like having another's account code, identification code, or other personal information embedded in the magnetic stripe thereof. Thus, for example, criminals may steal hundreds or thousands of legitimate credit card account numbers and manufacture many additional cards bearing the stolen information. These fraudulent cards are then usable by the criminals to purchase goods and to receive cash with the legitimate card holder and the card issuer left holding the bill.

Likewise, so called debit cards are becoming increasingly popular. These cards have stored thereon a certain amount of value for which the card owner has previously paid. For example, a subway rider may purchase a card good for X fares, with one fare being deducted from the card each time the owner rides the subway. Criminals have also been able to manipulate the data stored on these cards to defraud the merchants and others.

The ease in which criminals have been able to manufacture and/or manipulate known cards results from the existence of the easily altered magnetic stripe storage medium used by known cards. These magnetic stripes are easily programmed and reprogrammed using commonly available technology. Thus, there has been found a need in the plastic card industry to provide a more secure plastic card that is very difficult or impossible to fraudulently manipulate.

The likely successor to magnetic stripe cards is known as a memory or smart card. A smart card can generally be described as a card having an integrated circuit with memory that is capable of making decisions. The category of smart cards can be further divided into subcategories based on the type of memory or type of communication with an associated card reader. Types of smart cards include contact cards (cards requiring physical touch between the terminal reader and the surface of the card) and contactless cards (cards which interact with the terminal reader using a electromag-

2

netic coupling). Contactless cards may also be referred to as "proximity" cards. This technology may serve as a substitute for or be provided as an addition to the magnetic stripe on a card.

One specific type of smart card is a dual function contact/contactless microprocessor chip plastic card commonly referred to in the industry as a dual function card. This card utilizes a single microprocessor to control both physical contact and proximity features of the card.

While these smart cards have been found to have infinitely more capability than magnetic stripe cards as well as being more successful in preventing or limiting fraud, they are more difficult and expensive to manufacture relative to ordinary magnetic stripe cards. One of the biggest obstacles to the wide spread manufacture and use of smart cards has been the inability of card manufacturers to manufacture a smart card that meets all industry standards and specifications, such as those set by the International Standards Organization (ISO), that are sufficiently aesthetically pleasing (wherein the embedded electronics are hidden from view), and that have a sufficiently regular or flat surface such that one or both surfaces of the card may be printed on using the very popular and widespread dye sublimation technology.

Limitations to known plastic cards with embedded computer chips and electronics are that they a) are too thick to work in connection with existing card reading machinery (ATM machines, telephones, b) have a surface that is too irregular to properly and consistently receive dye sublimation printing, c) utilize manufacturing processes making the cards cost prohibitive. Moreover, prior attempts to manufacture a sufficiently thin plastic card including a computer chip embedded therein have resulted in a card with inferior aesthetic qualities such as the ability to see the embedded computer chip through the plastic.

Furthermore, due to the presence of both internal and surface electronics within the card, the manufacture of a dual function card presents its own unique set of obstacles and problems, different from the manufacture of cards with fully embedded electronics.

## SUMMARY OF THE INVENTION

The present invention is therefore directed to a hot lamination method for the manufacture of a plastic card having at least one electronic element embedded therein as well as at least one electronic element with an exposed contact surface and to such plastic cards. The card has an overall thickness in the range of 0.028 inches to 0.032 inches and comprises a plastic core having at least one electronic element embedded therein with at least one of the upper and lower surfaces of the core comprising a coating printed or otherwise applied thereon. A portion of the card's outer surface exposes a contact surface electronic element operatively connected to the card's internal electronics. An overlamine film is preferably provided over the coated surface of the core and the resulting card has a variation in thickness across the surfaces thereof of no greater than approximately 0.0005 inches.

The hot lamination method of the present invention comprises the steps of providing upper (first) and lower (second) plastic core sheets, positioning at least one electronic element between the first and second core sheets to thus form a core, and placing the core in a laminator and closing the laminator with minimal or no laminator ram pressure applied to the core. A heat cycle is applied to the core sheets in the laminator to cause complete or partial flow

6,036,099

3

of the plastic sheets. The laminator ram pressure is then increased in combination with the heat. A cooling cycle is then applied to the core in the laminator, preferably with an associated increase in ram pressure, and the core is removed from the laminator.

In the preferred embodiment, the laminated core next undergoes a controlled depth milling operation to expose one or more contact pads which comprise part of the internal, embedded electronic element.

In alternative embodiments, one of the plastic sheets contained a pre-formed window which is positioned over the contact pads, prior to lamination. A spacer, integral to the corresponding platen or separate therefrom, is utilized to prevent or limit the flow of plastic into the window region so as not to coat the contact pads with plastic during the card manufacturing process.

At least one surface of the core is then printed on using a printing press or similar printing apparatus, a sheet of overlamine film is placed on at least one side of the core, and the core is once again placed in a laminator. A heat cycle is applied to the core with its overlamine film, and a cooling cycle is thereafter applied, resulting in a sheet of plastic card stock from which one or more cards may be cut.

Contact surface elements are installed into the window region of a plastic card and in operable contact with contact pads.

The invention is also directed to a card manufactured in accordance with the above process which results in a plastic card having a thickness in the range of approximately 0.028 inches to 0.032 inches with a surface smoothness of at least approximately 0.0005 inches as is required by International Standards Organization (ISO) and American National Standards Institute (ANSI) standards.

The present invention provides numerous advantages over known plastic cards and known plastic card manufacturing processes, and includes the formation of a plastic card with electronic elements such as a computer chip embedded therein with a pleasing aesthetic appearance, having a sufficiently smooth and regular surface such that the card may receive dye sublimation printing, and possessing sufficient durability and characteristics to comply with all industry specifications and standards.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a plastic card in accordance with the present invention;

FIG. 2 is a perspective view of the card shown in FIG. 1, illustrating the embedded and exposed electronics incorporated into the card;

FIG. 2A is a side elevational view of the card core illustrating various electronic elements that may be embedded in a card in accordance with the present invention;

FIG. 3A is a cross sectional view of the card illustrated in FIG. 2, taken through section line 3A—3A.

FIG. 3B is a cross sectional view of the card illustrated in FIG. 2, taken through section line 3B—3B.

FIG. 4 is a perspective view of a plurality of electronic elements positioned on a sheet of plastic core stock and covered by a second sheet of plastic core stock.

FIG. 5 is a schematic cross sectional view illustrating a book comprising the core, containing electronics, as positioned in a laminator;

FIG. 5A is an enlarged cross-sectional view of the portion encircled in FIG. 5 for an alternative embodiment, utilizing a spacer, for producing a card according to the present invention;

4

FIG. 6 schematically illustrates the process of printing on the core;

FIG. 7 is a schematic cross sectional view illustrating the core with overlamine film, as placed in a laminator;

FIG. 8 is an exploded view of a plastic card produced by the process of the present invention.

#### DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to a plastic card including at least one electronic element embedded therein. The present invention also relates to a hot lamination process for the manufacture of plastic cards, and more particularly to a hot lamination process for the manufacturer of plastic cards that include an electronic element, such as a computer chip or other electronic element embedded therein. The electronic element may perform a wide variety of functions and take a wide variety of forms. Such cards, without regard to the particular electronic element embedded therein, will hereinafter be referred to as smart cards. The present invention also relates to a card formed in accordance with the invention.

In its preferred embodiment and as illustrated in FIGS. 1 and 2, the present invention relates to the manufacture of a dual function card, a particular type of smart card which utilizes a dual function contact/contactless microprocessor chip, as described previously herein. However, it will be appreciated by those skilled in the art, that the method of hot lamination described herein could easily be applied to other identity card or smart card applications.

Referring now to FIGS. 1, 2, and 2A there can be seen a plastic card 10 manufactured in accordance with the present invention and including an electronic element, generally 20, embedded therein. Card 10 includes an upper surface 12 and a lower surface 14. Electronic element 20 may take a wide variety of forms (microprocessor chip, circuit board, transponder, etc.) and perform a wide variety of functions. As shown in FIGS. 2, 2A, and 3A, electronic element 20 may comprise a read/write micro-chip 22 including a wire antenna 24 connected thereto, any other suitable electronic element. These electronic elements 20, 22 and 24 and their insertion into plastic cards is not new, however, the present invention provides a new hot lamination process for manufacturing plastic cards 10 with these electronic elements embedded therein such that the cards 10 are of a superior quality, meet all ISO and other industry specifications and standards, and are sufficiently smooth and otherwise is capable of receiving dye sublimation printing. Electronic elements such as these described are available from manufacturers such as Motorola and Philips Electronics.

Upper surface 12 contains a window or cavity 16 formed therein and intended to expose one or more contact pads 26 operatively connected to antenna 24. Upon formation of card 10 in accordance with the preferred embodiment, a microprocessor chip 22 is inserted into window 16 and in electrical connection with contact pads 26. This microprocessor chip may function as a "proximity" or radio frequency identification (RFID) card in conjunction with antenna 24 when electromagnetically used with a compatible terminal reader. Microprocessor chip 22 is also capable of function as a contact card, requiring physical contact between a compatible terminal reader and the surface of chip 22. It should be appreciated that the contact function of the card may be accomplished by any contact sensor whether integral to or physically separate from chip 22 and that window 16 may be formed anywhere on surfaces 12 and/or 14 as will accomplish the purposes of the invention.

6,036,099

5

Specifically, a card in accordance with the present invention has a thickness of approximately in the range of 0.028 inches to 0.032 inches with a surface smoothness of 0.0005 inches. In order to meet the ISO standards for such cards, these tolerances apply to the surface of the microprocessor chip 22 surface as well as to the surface of plastic portion of card 10. It is to be appreciated that cards having a thickness greater than 0.032 inches can easily be manufactured in accordance with the teachings herein while meeting all of the other criteria of the present invention. However, the foreseen product demand is for cards meeting the aforementioned standards.

As shown in FIG. 4, one or more cards 10 in accordance with the present invention may be manufactured by positioning an electronic element 20, including contact points 26, between first and second sheets of card stock 30, 32 to form a core 33. Preferably as shown, a plurality of cards are manufactured simultaneously, and accordingly a plurality of electronic elements 20 are positioned between the first and second sheets of plastic core stock 30, 32. When a plurality of electronic elements 20 are positioned between first and second sheets plastic core stock 30, 32, electronic elements 20 are properly positioned relative to one another such that a plurality cards may be cut from the resulting card stock.

Plastic core sheets 30, 32 may be provided by a wide variety of plastics, the preferred being polyvinyl chloride (PVC) having a thickness in the range of 0.007 inches to 0.024 inches and preferably having a thickness of approximately 0.0125 inches each. Those skilled in the art will recognize that the thickness of the plastic core sheets will depend somewhat upon the thickness of the one or more electronic elements that are to be embedded therebetween if ISO standards are intended to be met. Other suitable plastics that may be utilized include polyester, acrylonitrile-butadiene-styrene (ABS), and any other suitable plastic.

Subsequent to placing one or more electronic elements 20 between the first and second sheets 30, 32 of plastic core stock to form a core 33, this core 33 is placed in a laminator apparatus 40 of the type well known in the art of plastic card manufacturing. As is shown in FIG. 5, laminator 40 includes upper and lower platens 42, 44 for applying ram pressure to an article positioned therebetween. In addition to the ability to apply ram pressure, laminator 40 is preferably of the type having controlled platens 42, 44 that may provide both heat and chill cycles and preferably includes cycle timer to regulate cycle time. Core 33 is positioned between first and second laminating plates 50, 52, one of which is preferably matte finished to provide laminated core 33 with at least one textured outer surface. First and second laminating pads 60, 62 are positioned outside of the laminating plates 50, 52, and first and second steel plates 70, 72 are likewise positioned outside of pads of 60, 62 and the entire assembly forms a book 35 for being positioned in laminator 40 between platens 42, 44.

Once book 35 is positioned in laminator 40 as shown in FIG. 5, the first lamination cycle is initiated by closing laminator platens 42, 44, preferably applying little or no ram pressure to book 35. This is preferably done using hydraulic pressure, and a pressure not to exceed about 10 pounds per square inch is believed sufficient for most applications.

A laminator heat cycle is initiated, bringing the temperature of platens 42, 44 up to a range of 275° F. to 400° F., and most preferably up to a range of 300° F. to 370° F. for a period of ranging between 1 to 20 minutes, but preferably greater than 5 minutes, and most preferably in the range of 7 to 10 minutes for PVC material. It must be understood that

6

the temperatures recited herein are by means of example. The use of thermoplastic material other than PVC or the presence of pigments in the core material may require modification of the heat cycle temperature.

Once the heat cycle has been applied to book 35 as is set forth above, the ram pressure of laminator 40 is increased to facilitate the flow of the plastic core sheets 30, 32 so that the one or more electronic elements 20 become encapsulated thereby, and so that sheets 30, 32 form a uniform core 33 with upper and lower surfaces 34, 35. The ram pressure translates into an effective pressure on core 33 in the range of 200 to 450 psi and preferably in the range of 250 to 350 psi. As can be expected temperature and pressure are inversely related to one another. In other words a lamination cycle at a higher temperature will require less pressure to be applied to core 33, and conversely a lower temperature heat cycle will require increased ram pressure. Damage to the electronic components can result from excessive ram pressure on the core while insufficient ram pressure will likely cause an inadequate flow of the plastic resulting in air pockets or an irregular card surface.

As mentioned, the use of matte finished laminator plates 50, 52 provides surfaces 34, 35 with a slightly roughened or textured quality which will facilitate the application of a coating thereto as is discussed below. The ram pressure applied during the heat cycle and the length of the heat cycle may vary, depending especially upon the size of sheets 30, 32. For example, the cycle time may be in the range of 10-15 minutes. In one example, at a temperature of approximately 320 degrees Fahrenheit, a ram pressure of 940.135 pounds per square inch (p.s.i.), producing a pressure of about 275 psi at the core 33 surface, was applied for 10-15 minutes to form a uniform core 33, using sheets 30, 32 of a size in the range of 12 inches by 24 inches to 24 inches by 36 inches.

Subsequent to the above heat cycle, laminator 40 applies a chill cycle to book 35 during which time the ram pressure of the laminator 40 is increased, preferably by approximately 10-40% and most preferably about 25% until the platens 42, 44 have cooled so as to return the core material to a solid state. In the preferred method the platens 42, 44 are cooled to approximately 40° F. to 65° F. for approximately 10-15 minutes. Core 33 may then be removed from laminator 40 for additional processing.

Subsequent to the removal of core 33 from laminator 40, and as illustrated in FIG. 6, core 33 is coated on at least one of its upper and lower surfaces 34, 35 with a layer of printing ink 36. This may be accomplished using a wide variety of printing techniques such as offset printing, letterpress printing, screen printing, roller coating, spray printing, litho-printing, and other suitable printing techniques. As shown in FIG. 6, core 33 is fed in the direction indicated with arrow A through a printing press, a lithographic printer, or a similar apparatus 80. This printing step is performed to coat at least one surface 34, 35 of core 33 with a layer of aesthetically pleasing ink 36. This layer of ink 36 can also serve to cosmetically hide the one or more electronic elements 20 that are embedded within core 33, and prevent these one or more electronic elements 20 from showing through the relatively thin core 33. In this manner, the one or more electronic elements 20 encapsulated in core 33 are completely hidden from view without requiring the plastic used in the manufacture core 33 to be excessively thick (exceeding ISO standards for cards of this type).

Referring now to FIG. 7, the final preferred, but optional processing of core 33, which now comprises a layer of ink 36 or the like on at least one surface 34, 35 thereof, is



6,036,099

7

schematically illustrated. An overlamine layer such as clear overlamine film 38 is positioned on at least one ink coated surface 34,35 of core 33, and preferably core 33 is positioned between two similar sheets of overlamine film 38,39 as shown. Overlamine film is very thin, for example in the range of 0.0015" thick. A book 135 is then constructed for insertion into laminator 40 as is schematically illustrated in FIG. 7. Book 135 comprising core 33, including at least one layer of ink 36 and at least one layer of overlamine film 38, 39 is positioned between laminating plates which are preferably highly polished plates such as mirror finished stainless steel plates 91, 92. Book 135 also comprises first and second laminating pads 60, 62 and first and second steel plates 70, 72 as is discussed above in relation to FIG. 7.

When book 135 is positioned between upper and lower platens 42,44 of laminator 40 as shown in FIG. 7, the laminator is closed and a heat cycle in the range of 175° F. to 300° F., and most preferably in the range of 180° F. to 275° F., is applied to book 135 for a period of 10 to 25 minutes to produce a pressure on book 135 of between 200 to 450 psi, preferably 250-350 psi, with a ram pressure that varies depending upon sheet size or the ram size of the laminator 40, but which is typically approximately 1000 p.s.i. with an 18 inch diameter ram. This step causes the overlamine layer 38 to flow in order to produce a uniform protective layer over the printing.

The laminator 40 is then caused to execute a chill cycle, preferably with a corresponding increase in ram pressure. For example, the chill temperature may be in the range of 40° F. to 65° F. and last for a period of 10 to 25 minutes. However, any combination of temperature and time which permits the re-solidification of the overlamine layer 38 may be used. A ram pressure increase of approximately 10 to 40% over the pressure used for the heat cycle has been found to be preferable, with a pressure increase of approximately 25% being most desirable.

It is important to note that the use of pressure, or more significantly temperature, in the second lamination cycle should only affect the overlamine layer 38 and should not cause softening or re-flow of plastic core 33. In lieu of this preferred overlamination process, it is to be understood that colorfast inks may not require an overlamine layer or that alternative overlaminates such as those applied by spray, silk screening or roll on may be used.

Subsequent to the above described second lamination cycle, a sheet of plastic card stock is provided which comprises at least core 33 with at least one surface 34,35 thereof covered by a layer of ink 36, and with at least one surface 34,35 thereof covered by a layer of overlamine film 38, 39.

Preferably plastic card stock manufactured in accordance with the present invention comprises core 33 covered on both surfaces 34,35 with a layer of ink 36 which is positioned between layers of overlamine film 38,39, all of which has been laminated together as described and as shown in FIG. 8. One or more cards 10 then may be cut from the resulting plastic card stock and card 10 will have a thickness in the range of 0.028 inches to 0.032 inches with variation in overall thickness across the surfaces 12, 14 thereof being no greater than approximately 0.0005 inches. The one or more cards 10 can thus be said to have a glossy surface smoothness of approximately 0.0005 inches or better. Thus, a card 10 manufactured in accordance with the present invention includes at least one surface 12,14 at 65 preferably both surfaces 12,14 that are sufficiently smooth, glossy and regular to receive dye sublimation printing.

8

In the preferred embodiment, each card 10 undergoes a controlled-depth milling operation to form a window or cavity 16 and to expose one or more of the contact pads 26 connected to the antenna 24. Thereafter, a microprocessor chip 22 having a contact surface is inserted into the cavity and in electronic contact with contact pads 26. Chip 22 may be attached to contact pads 26 by known means such as conductive adhesives (including those cured by UV or sonic energy) or low temperature solder. The overall thickness of the card including the area occupied by chip 22 meets ISO standards and is capable of operation in compatible physical readers.

In an alternative embodiment, a cavity or window 16 is formed in the first or second sheet of plastic core stock, prior to the first lamination step. The core stock is positioned over the electronic element, generally 20, to expose one or more contact pads 26. This may also be done using electronic elements wherein microprocessor chip 22 is already attached to contact pads 26 and/or antenna 24 in which case the cavity is positioned over and around chip 22. As shown in FIG. 5a, a spacer 90 is inserted into cavity 16 and over contact pads 26 or chip 22. The spacer 90 may be integral to one of the matte laminating plates 50, 52 or separate therefrom and made of any suitable non-stick material such as Teflon™. Spacer 90 is utilized to prevent or limit the flow of plastic into cavity 16 during the lamination process so as not to cover contact pads 26 or chip 22 with plastic. When spacer 90 is non-integral with matte laminating plate 50 or 52 it may be removed or cut-away after either the lamination or overlamination process to expose cavity 16 and allow microchip 22 to be inserted therein and retained by such means as are known in the art, including solder or adhesives. In this embodiment where the chip is installed prior to lamination, when viewed in cross-section the outer surface of chip 22 is below the upper surface 34 or core sheet 35 prior to lamination, thus core sheets will accept the majority of applied pressure from the laminator. Spacer 90 provides further protection. As the core material softens, the plastic will flow around spacer 90 and chip 22 and the distance between the outer surface of chip 22 and the upper surface of core sheet 35 will decrease.

Those skilled in the art will recognize that the foregoing description has set forth the preferred embodiment of the invention in particular detail and it must be understood that numerous modifications, substitutions, and changes may be undertaken without departing from the true spirit and scope of the present invention as defined by the ensuing claims.

What is claimed is:

1. A process for incorporating at least one electronic element in the manufacture of a plastic card, comprising the steps of:

- (a) providing first and second plastic core sheets;
- (b) positioning said at least one electronic element in the absence of a non-electronic carrier directly between said first and second plastic core sheets to form a core, said plastic core sheets defining a pair of inner and outer surfaces of said core;
- (c) positioning said core in a laminator apparatus, and subjecting said core to a heat and pressure cycle; said heat and pressure cycle comprising the steps of:
  - (i) heating said core for a first period of time;
  - (ii) applying a first pressure to said core for a second period of time such that said at least one electronic element is encapsulated by said core;
  - (iii) cooling said core while applying a second pressure to said core;

6,036,099

9

(d) coating at least one of said outer surfaces of said core with a layer of ink;

(e) milling a region of said core to a controlled depth so as to form a cavity which exposes at least one contact pad of said electronic element.

2. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said laminator apparatus has first and second laminating plates, at least one of said first and second laminating plates having a matte finish for creating a textured surface on at least one of said outer surfaces of said core.

3. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 2, wherein each of said first and second laminating plates has a matte finish for creating said textured surface on both of said outer surfaces of said core.

4. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said first and second plastic core sheets are made from a material selected from the group consisting of polyvinyl chloride, polyester, and acrylonitrile-butadiene-styrene, each of said sheets having a thickness in the range of 0.007 to 0.024 inch.

5. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 5, wherein said first and second plastic core sheets have a thickness of approximately 0.0125 inch.

6. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said second pressure is greater than said first pressure.

7. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 6, wherein said second pressure ranges from about 10% to about 40% greater than said first pressure.

8. A hot lamination process as recited in claim 1 having a further step following step (d), said step comprising: positioning said core in a laminator apparatus with a layer of overlamine film on at least one of said upper and lower surfaces of said core and laminating said layer of overlamine film to said core in said laminator to thereby form a sheet of plastic card stock.

9. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said core is heated in step (c)(i) to a temperature in the range of 275° F. to 400° F. and said first period of time is at least five (5) minutes.

10. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said first pressure is approximately 450 p.s.i. and said second period of time is at least 10 minutes.

11. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said step (d) is carried out utilizing a printing press.

12. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said step (d) is carried out utilizing a coating technique selected from the group consisting of silk screen printing, offset printing, letterpress printing, screen printing, roller coating, spray printing and litho-printing.

10

13. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said step (e) of applying a layer of overlamine film comprises the further steps of:

(a) positioning an overlamine film on at least one ink coated surface of said core;

(b) subjecting said core to a second heat and pressure cycle comprising the steps of:

(i) heating said core to a temperature between approximately 175° F. to 300° F. for approximately 10 to 25 minutes;

(ii) applying approximately 1000 p.s.i. pressure to said core; and

(iii) cooling said core to a temperature in the range of approximately 40° F. to 65° F. for approximately 10 to 25 minutes.

14. A hot lamination process is recited in claim 1 comprising the further step of inserting an electronic contact element into said cavity.

15. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said at least one electronic element is a micro-chip and an associated circuit board antenna or an associated wire antenna.

16. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said at least one electronic element is a read/write integrated chip and an associated antenna.

17. A process for incorporating at least one electronic element having at least one electronic subcomponent in the manufacture of a plastic card, comprising the steps of:

(a) providing first and second plastic core sheets, at least one core sheet having a cavity formed therein;

(b) positioning said at least one electronic element in the absence of a non-electronic carrier between said first and second plastic core sheets to form a layered core; said plastic core sheets defining a pair of inner and outer surface of said core, and said cavity positioned so as to expose said at least one electronic subcomponent therein;

(c) inserting a spacer into said cavity, said spacer substantially filling said cavity and covering said at least one electronic subcomponent;

(d) positioning said core in a laminator apparatus, and subjecting said core to a heat and pressure cycle, said heat and pressure cycle comprising the steps of:

(i) heating said core for a first period of time;

(ii) applying a first pressure to said core for a second period of time such that said at least one electronic element is encapsulated by said core;

(iii) cooling said core while applying a second pressure to said core;

(e) coating at least one of said outer surfaces of said core with a layer of ink;

(f) removing said spacer from the cavity of said core.

18. A hot lamination process as recited in claim 17, wherein said electronic sub-component comprises one or more elements from the group consisting of a microprocessor chip, a contact pad, a transponder and a contact sensor.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
CERTIFICATE OF CORRECTION

PATENT NO. : 6,036,099  
DATED : March 14, 2000  
INVENTOR(S) : Keith R. Leighton

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:


Column 1,

Line 7, replace "Oct. 7, 1996" with -- Oct. 7, 1996, which claimed the benefit of provisional application serial no 60/005,685, filed on October 17, 1995, filed on October 17, 1995. This application claims the benefit of provisional application serial no. 60/024,255, filed August 21, 1996 --.

Signed and Sealed this

Twenty-fourth Day of September, 2002

Attest:



Attesting Officer

JAMES E. ROGAN  
Director of the United States Patent and Trademark Office

## Exhibit C



US006214155B1

(12) **United States Patent**  
Leighton

(10) Patent No.: **US 6,214,155 B1**  
(45) Date of Patent: **Apr. 10, 2001**

(54) **RADIO FREQUENCY IDENTIFICATION CARD AND HOT LAMINATION PROCESS FOR THE MANUFACTURE OF RADIO FREQUENCY IDENTIFICATION CARDS**

(76) Inventor: **Keith R. Leighton, 2817 Fulmer Rd., Lorain, OH (US) 44053**

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/158,290**

(22) Filed: **Sep. 22, 1998**

#### Related U.S. Application Data

(63) Continuation of application No. 08/727,789, filed on Oct. 7, 1996, now Pat. No. 5,817,207.

(60) Provisional application No. 60/005,685, filed on Oct. 17, 1995.

(51) Int. Cl.<sup>7</sup> ..... **B32B 31/20**

(52) U.S. Cl. .... **156/298; 156/312**

(58) Field of Search ..... **156/298, 312**

(56) **References Cited**

#### U.S. PATENT DOCUMENTS

3,994,225	11/1976	Sitzberger	101/485
4,450,024	5/1984	Haghiri-Tehran et al.	156/108
4,701,236	10/1987	Vieilledent	156/252
4,792,843	12/1988	Haghiri-Tehrani et al.	257/679
4,795,898	1/1989	Bernstein et al.	235/487
4,841,134	6/1989	Hida et al.	235/488

4,980,802	12/1990	Champagne et al.	361/764
5,067,008	11/1991	Yanaka et al.	257/703
5,097,117	3/1992	Champagne et al.	235/488
5,173,840	12/1992	Kodai et al.	361/737
5,208,450	5/1993	Uenishi et al.	235/492
5,268,699	12/1993	Laute et al.	343/702
5,272,596	12/1993	Honore et al.	361/633
5,396,650	3/1995	Terauchi	455/38.2
5,412,192	5/1995	Hoss	235/380
5,438,750	8/1995	Venambre	29/829
5,567,362	10/1996	Grun	264/1.31
5,809,633	9/1998	Mundigl et al.	29/600.3


Primary Examiner—Francis J. Lorin

(74) Attorney, Agent, or Firm—Oldham & Oldham Co., L.P.A.

(57) **ABSTRACT**

A plastic card, such as a radio frequency identification card, including at least one electronic element embedded therein and a hot lamination process for the manufacture of radio frequency identification cards and other plastic cards including a micro-chip embedded therein. The process results in a card having an overall thickness in the range of 0.028 inches to 0.032 inches with a surface suitable for receiving dye sublimation printing—the variation in card thickness across the surface is less than 0.0005 inches. A card manufactured in accordance with the present invention also complies with all industry standards and specifications. Also, the hot lamination process of the present invention results in an aesthetically pleasing card. The invention also relates to a plastic card formed in accordance with the hot lamination process of the present invention.

16 Claims, 3 Drawing Sheets





U.S. Patent

Apr. 10, 2001

Sheet 1 of 3

US 6,214,155 B1




FIG. - 1




FIG. - 2




FIG. - 3A




FIG. - 3B




FIG. - 3C

U.S. Patent

Apr. 10, 2001

Sheet 2 of 3

US 6,214,155 B1




FIG. - 4




FIG. - 5




FIG. - 6







FIG. - 7

U.S. Patent

Apr. 10, 2001

Sheet 3 of 3

US 6,214,155 B1



US 6,214,155 B1

1

# RADIO FREQUENCY IDENTIFICATION CARD AND HOT LAMINATION PROCESS FOR THE MANUFACTURE OF RADIO FREQUENCY IDENTIFICATION CARDS

This application is a continuation of Ser. No. 08/727,789, now U.S. Pat. No. 5,817,207 which claim the benefit of provision of application 60/005,685 filed on Oct. 17, 1995.

## FIELD OF THE INVENTION

The present invention relates generally to plastic cards and the manufacture thereof, and more particularly to radio frequency identification (RFID) cards and the manufacture of RFID cards that conform to industry size and performance standards and conventions and that have a superior outer surface to known RFID cards such that card may receive dye sublimation printing or the like.

## BACKGROUND OF THE INVENTION

As the use of plastic cards for credit cards, automated teller machine (ATM) cards, identification cards, and like continues to become more widespread, the problems associated with the use of such cards correspondingly increase. Credit card fraud and identification card fraud are becoming larger problems everyday, and this fraud has introduced uncertainties into our systems of commerce and our security systems. Using easily available technology, criminals are able to manufacture credit/debit cards, ATM cards, identification cards, and the like having another's account code, identification code, or other personal information embedded in the magnetic stripe thereof. Thus, for example, criminals may steal hundreds or thousands of legitimate credit card account numbers and manufacture many additional cards bearing the stolen information. These fraudulent cards are then usable by the criminals to purchase goods and to receive cash with the legitimate card holder and the card issuer left holding the bill. Likewise, so called debit cards are becoming increasingly popular. These cards have stored thereon a certain amount of value for which the card owner has previously paid. For example, a subway rider may purchase a card good for 50 fares, with one fare being deducted from the card each time the owner rides the subway. Criminals have also been able to manipulate the data stored on these cards to defraud the merchants and others.

The ease in which criminals have been able to manufacture and or manipulate known cards results from the existence of the easily altered magnetic stripe storage medium used by known cards. These magnetic stripes are easily programmed and reprogrammed using commonly available technology. Thus, there has been found a need in the plastic card industry to provide a more secure plastic card that is very difficult or impossible to fraudulently manipulate. The most likely solution to the above-noted problems associated with known plastic cards is the RFID card and other cards including computer chips embedded therein rather than, or in addition to, a magnetic stripe. While these RFID cards and like have been found to be successful in preventing or limiting fraud, they are more difficult and expensive to manufacture relative to ordinary magnetic stripe cards. One of the biggest obstacles to the wide spread manufacture and use of RFID cards has been the inability of card manufacturers to manufacture an RFID card that meets all industry standards and specifications, such as those set by the International Standards Organization (ISO), that are sufficiently aesthetically pleasing (wherein the embedded electronics are

2

hidden from view), and that have a sufficiently regular or flat surface such that one or both surfaces of the card may be printed on using the very popular and widespread dye sublimation technology. Known plastic cards with computer chips and like embedded therein are too thick to work in connection with existing card reading machinery (ATM machines, telephones, and like) and have a surface that is too irregular to properly and consistently receive dye sublimation printing. Furthermore, prior attempts to manufacture a sufficiently thin plastic card including a computer chip embedded therein have resulted in a card with inferior aesthetic qualities such as the ability to see the embedded computer chip through the plastic.

## SUMMARY OF THE INVENTION

The present invention is therefore directed to a plastic card having at least one electronic element embedded therein and to a hot lamination method for the manufacture of plastic cards including at least one electronic element therein. The card has an overall thickness in the range of 0.028 inches to 0.032 inches and comprises a plastic core having at least one electronic element embedded therein with at least one of the upper and lower surfaces of the core comprising a coating printed or otherwise applied thereon. An overlamine film is preferably provided over the coated surface of the core and the resulting card has a variation in thickness across the surfaces thereof of no greater than approximately 0.0005 inches. The hot lamination method of the present invention comprises the steps of providing first and second plastic core sheets, positioning at least one electronic element between the first and second core sheets to thus form a core, and placing the core in a laminator and closing the laminator without applying laminator ram pressure to the core. A heat cycle is applied to the core sheets in the laminator thus liquefying or partially liquefying the sheets. The laminator ram pressure is then increased in combination with the heat. A cooling cycle is then applied to the core in the laminator, preferably with an associated increase in ram pressure, and the core is removed from the laminator. At least one surface of the core is then printed on using a printing press or similar printing apparatus, a sheet of overlamine film is placed on at least one side of the core, and the core is then again placed in a laminator. A heat cycle is applied to the core with its overlamine film, and a cooling cycle is thereafter applied, resulting in a sheet of plastic card stock from which one or more cards may be cut. The invention is also directed to a card manufactured in accordance with the above process which results in a plastic card having a thickness in the range of approximately 0.028 inches to 0.032 inches with a surface smoothness of at least approximately 0.0005 inches as is required by ISO and American National Standards Institute (ANSI) standards.

The present invention provides numerous advantages over known plastic cards and known plastic card manufacturing processes, including the formation of a plastic card with electronic elements such as a computer chip embedded therein with a pleasing aesthetic appearance, with a sufficiently smooth and regular surface such that the card may receive dye sublimation printing, and with sufficient durability and characteristics to comply with all industry specifications and standards.

## BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a top plan view of a plastic card in accordance with the present invention;

FIG. 2 is a side elevational view of the card shown in FIG. 1;

US 6,214,155 B1

3

FIGS. 3A-3C are top plan views of various electronic elements that may be embedded in a card in accordance with the present invention;

FIG. 4 is an exploded, schematic view of an electronic element position between two plastic core sheets to form a core;

FIG. 5 is a top plan view of a plurality of electronic elements positioned on a sheet of plastic core stock such that they may be covered by a similar sheet of core stock;

FIG. 6 is a schematic cross-sectional view of one or more electronic elements positioned between sheets of plastic core stock;

FIG. 7 schematically illustrates a book comprising the core, as it is positioned in a laminator apparatus;

FIG. 8 schematically illustrates the core as it is being printed on after removal from the laminator using a printing press or similar printing apparatus;

FIG. 9 is a cross-sectional view schematically illustrating the application of an overlamine film to at least one side of the core;

FIG. 10 schematically illustrates the core with overlamine film, as it is placed in a laminator for final processing to form a sheet of card stock.

#### DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to a plastic card including at least one electronic element embedded therein. The present invention also relates to a hot lamination process for the manufacture of plastic cards, and more particularly to a hot lamination process for the manufacture of plastic cards that include an electronic element, such as a computer chip or other electronic element embedded therein. The electronic element may perform a wide variety of functions and take a wide variety of forms. Such cards, without regard to the particular electronic element embedded therein, will hereinafter be referred to as radio frequency identification (RFID) cards. The present invention also relates to a card formed in accordance with the invention.

Referring now to FIG. 1, there can be seen a plastic RFID card 10 manufactured in accordance with the present invention and including an electronic element 20 embedded therein. Card 10 includes an upper surface 12 and a lower surface 14. Electronic element 20 may take a wide variety of forms and perform a wide variety of functions. As shown in FIGS. 3A-3C respectively, electronic element 20, 20', 20" may be provided by a micro-chip 22 including a wire antenna 24 connected thereto, a micro-chip 22' and a circuit board antenna 24', a read/write micro-chip 22" and a wire coil antenna 24", or any other suitable electronic element. These electronic elements 20, 20', 20" and their insertion into plastic cards is not new, however, the present invention provides a new hot lamination process for manufacturing plastic cards 10 with these electronic elements 20, 20', 20" embedded therein such that the cards 10 are of a superior quality, such that the cards 10 meet all ISO and other industry specifications and standards, in such that at least one of the upper and lower surfaces 12, 14 of card 10 is sufficiently smooth and is otherwise capable of receiving dye sublimation printing. Specifically, a card in accordance with the present invention has a thickness of approximately in the range of 0.028 inches to 0.032 inches with a surface smoothness of 0.0005 inches.

As shown in FIGS. 4-10 one or more cards 10 in accordance with the present invention may be manufactured

4

by positioning an electronic element 20 between first and second sheets of card stock 30, 32 to form a core 33. Preferably is shown in FIGS. 5-10, a plurality of cards are manufactured simultaneously, in thus, a plurality of electronic elements 20 are positioned between the first and second sheets of plastic core stock 30, 32 (only the second sheet 32 begin shown in FIG. 5 for clarity). When a plurality of electronic elements 20 are positioned between first and second sheets plastic core stock 30, 32, electronic elements 20 are properly positioned relative to one another such that a plurality cards may be cut from the resulting card stock. Plastic core sheets 30, 32 may be provided by a wide variety of plastics, the preferred being polyvinyl chloride (PVC) having a thickness in the range of 0.007 inches to 0.024 inches and preferably having a thickness of approximately 0.0125 inches each. Those skilled in the art will recognize that the thickness of the plastic core sheets will depend upon the thickness of the one or more electronic elements that are to be embedded therebetween. Other suitable plastics that may be utilized include polyester, acrylonitrile-butadiene-styrene (ABS), and any other suitable plastic.

Subsequent to placing one or more electronic elements 20 between the first and second sheets 30, 32 of plastic core stock to form a core 33, this core 33 is placed in a laminator apparatus 40 of the type well known in the art of plastic card manufacturing. As is shown in FIG. 7, laminator 40 includes upper and lower platens 42, 44 for applying ram pressure to an article positioned therebetween. In addition to the ability to apply ram pressure, laminator 40 is preferably of the type having controlled platens 42, 44 that may provide both heat and chill cycles and preferably includes cycle timer to regulate cycle time. Core 33 is positioned between first and second laminating plates 50, 52, one of which is preferably matte finished to provide laminated core 33 with at least one textured outer surface. First and second laminating pads 60, 62 are positioned outside of the laminating plates 50, 52, and first and second steel plates 70, 72 are likewise positioned outside of pads of 60, 62 and the entire assembly forms a book 35 for being positioned in laminator 40 between platens 42, 44.

Once book 35 is positioned in laminator 40 as shown in FIG. 7, the first lamination cycle is initiated by closing laminator platens 42, 44, preferably applying little or no ram pressure to book 35. A laminator heat cycle is initiated, bringing the temperature of platens 42, 44 up to a range of 275° F. to 400° F., and most preferably up to a range of 300° F. to 370° F. for a period of greater than 5 minutes, and preferably in the range of 7 to 10 minutes. Once the heat cycle has been applied to the book 35 as is set forth above, the ram pressure of laminator 40 is increased to facilitate the flow of the plastic core sheets 30, 32 so that the one or more electronic elements 20 are encapsulated there by, and so that sheets 30, 32 form a uniform core 33 (seen most clearly in FIGS. 8-10) with upper and lower surfaces 34, 35. As mentioned, the use of matte finished laminator plates 50, 52 provides surfaces 34, 35 with a slightly roughened or textured quality which will facilitate the application of a coating thereto as is discussed below. The ram pressure applied during the heat cycle and the length of the heat cycle may vary, depending especially upon the size of sheets 30, 32. For example, the cycle time may be in the range of 10-15 minutes. In one example, a ram pressure of 940.135 pounds per square inch (p.s.i.) was applied for 10-15 minutes to form a uniform core 33, using sheets 30, 32 of a size in the range of 12 inches by 24 inches to 24 inches by 36 inches.

Subsequent to the above heat cycle, laminator 40 applies a chill cycle to book 35 during which time the ram pressure



US 6,214,155 B1

5

of the laminator 40 is increased, preferably by approximately 25% until the platens 42, 44 have cooled to approximately 40° F. to 65° F. for approximately 10-15 minutes. Core 33 may then be removed from laminator 40 for additional processing.

Subsequent to the removal of core 33 from laminator 40, and as illustrated in FIG. 8, core 33 is coated on at least one of its upper and lower surfaces 34, 35 with a layer of printing ink 36. This may be accomplished using a wide variety of printing techniques such as offset printing, letterpress printing, screen printing, roller coating, spray printing, litho-printing, and other suitable printing techniques. As shown in FIG. 8, core 33 is fed in the direction indicated with arrow A through a printing press, a lithographic printer, or a similar apparatus 80. This printing step is performed to coat at least one surface 34, 35 of core 33 with a layer of aesthetically pleasing ink 36. This layer of ink 36 cosmetically hides the one or more electronic elements 20 that are embedded within core 33, and prevents these one or more electronic elements 20 from showing through the relatively thin core 33. In this manner, the one or more electronic elements 20 encapsulated in core 33 are completely hidden from view without requiring the plastic used in the manufacture of core 33 to be excessively thick.

Referring now to FIGS. 9-10, the final processing of core 33, which now comprises a layer of ink 36 or the like on at least one surface 34, 35 thereof, is schematically illustrated. A layer of overlamine film such as clear overlamine film 38, 39 is positioned on at least one ink coated surface 34, 35 of core 33, and preferably core 33 is positioned between two similar sheets of overlamine film 38, 39 as shown. Overlamine film is very thin, for example in the range of 0.0015" thick. A book 135 is then constructed for insertion into laminator 40 as is schematically illustrated FIG. 10. Book 135 comprising core 33, including at least one layer of ink 36 and at least one layer of overlamine film 38, 39 is positioned between laminating plates which are preferably highly polished plates such as mirror finished stainless steel plates 90, 92. Book 135 also comprises first and second laminating pads 60, 62 and first and second steel plates 70, 72 as is discussed above in relation to FIG. 7.

When book 135 is positioned between upper and lower platens 42, 44 of laminator 40 as shown in FIG. 10, the laminator is closed and a heat cycle in the range of 175° F. to 300° F., and most preferably in the range of 180° F. to 275° F., is applied to book 135 for a period of 10 to 25 minutes with a ram pressure that varies depending upon sheet size or the ram size of the laminator 40, but which is typically approximately 1000 p.s.i. with an 18 inch diameter ram. The laminator 40 is then caused to execute a chill cycle, preferably with a corresponding increase in ram pressure. For example, the chill temperature may be in the range of 40° F. to 65° F. and last for a period of 10 to 25 minutes. A ram pressure increase of approximately 25% over the pressure used for the heat cycle has been found to be most preferable.

Subsequent to the above described second lamination cycle as illustrated in FIG. 10, a sheet of plastic card stock is provided which comprises at least core 33 with at least one surface 34, 35 thereof covered by a layer of ink 36, and with at least one surface 34, 35 thereof covered by a layer of overlamine film 38, 39. Preferably plastic card stock manufactured in accordance with the present invention comprises core 33 covered on both surfaces 34, 35 with a layer of ink 36 which is positioned between layers of overlamine film 38, 39, all of which has been laminated together as described. One or more cards 10 then may be cut

6

from the resulting plastic card stock and card 10 will have a thickness in the range of 0.028 inches to 0.032 inches with variation in overall thickness across the surfaces 12, 14 thereof being no greater than approximately 0.0005 inches. The one or more cards 10 can thus be said to have a surface smoothness of approximately 0.0005 inches or better. Thus, a card 10 manufactured in accordance with the present invention includes at least one surface 12, 14 at preferably both surfaces 12, 14 that are sufficiently smooth and regular to receive dye sublimation printing.

Those skilled in the art will recognize that the foregoing description has set forth the preferred embodiment of the invention in particular detail and it must be understood that numerous modifications, substitutions, and changes may be undertaken without departing from the true spirit and scope of the present invention as defined by the ensuing claims.

What is claimed is:

1. A process for incorporating at least one electronic element in the manufacture of a plastic card, comprising the steps of:

- (a) providing first and second plastic core sheets;
- (b) positioning said at least one electronic element in the absence of a non-electronic carrier directly between said first and second plastic core sheets to form a core, said plastic core sheets defining a pair of inner and outer surfaces of said core;
- (c) positioning said core in a laminator apparatus, and subjecting said core to a heat and pressure cycle, said heat and pressure cycle comprising the steps of:
  - (i) heating said core for a first period of time;
  - (ii) applying a first pressure to said core for a second period of time such that said at least one electronic element is encapsulated by said core;
  - (iii) cooling said core while applying a second pressure to said core;
- (d) applying a layer of overlamine film to at least one of said outer surfaces of said core.

2. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said laminator apparatus has first and second laminating plates, at least one of said first and second laminating plates having a matte finish for creating a textured surface on at least one of said outer surfaces of said core.

3. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 2, wherein each of said first and second laminating plates has a matte finish for creating said textured surface on both of said outer surfaces of said core.

4. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said first and second plastic core sheets are made from a material selected from the group consisting of polyvinyl chloride, polyester, and acrylonitrile-butadiene-styrene, each of said sheets having a thickness in the range of 0.007 to 0.024 inch.

5. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 4, wherein said first and second plastic core sheets have a thickness of approximately 0.0125 inch.

6. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said second pressure is greater than said first pressure.

7. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in

US 6,214,155 B1

7

claim 6, wherein said second pressure is at least approximately 25% greater than said first pressure.

8. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said core is heated in step (c)(i) to a temperature in the range of 275° F. to 400° F. and said first period of time is at least five (5) minutes.

9. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said first pressure is approximately 1000 p.s.i. and said second period of time is at least 10 minutes.

10. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said step (d) of applying a layer of overlamine film comprises the further steps of:

(a) positioning an overlamine film on at least one surface of said core;

(b) subjecting said core to a second heat and pressure cycle comprising the steps of:

(i) heating said core to a temperature between approximately 175° F. to 300° F. for approximately 10 to 25 minutes;

(ii) applying approximately 1000 p.s.i. pressure to said core, and

(iii) cooling said core to a temperature in the range of approximately 40° F. to 65° F. for approximately 10 to 25 minutes.

11. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said at least one electronic element is a micro-chip and an associated wire antenna.

12. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in

8

claim 1, wherein said at least one electronic element is a micro-chip and an associated circuit board antenna.

13. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said at least one electronic element is a read/write integrated chip and an associated antenna.

14. A plastic card constructed in accordance with claim 1.

15. A hot lamination process for the manufacture of plastic cards, said process comprising the steps of:

(a) providing first and second plastic core sheets;

(b) positioning at least one electronic element in the absence of a non-electronic carrier directly between said first and second plastic core sheets to form a layered core;

(c) positioning said core in a laminator apparatus, and subjecting said core to a heat and pressure cycle, said heat and pressure cycle comprising the steps of:

(i) heating said core in said laminator, in the presence of a minimal first ram pressure, to a temperature which causes controlled flow of said plastic which makes up said first and second plastic core sheets;

(ii) applying a second pressure uniformly across said core for encapsulating said at least one electronic element within said controlled flow plastic;

(iii) subsequently cooling said core in conjunction with the concurrent application of a third pressure uniformly across said core, said core including and upper and lower surfaces.

16. The method as recited in claim 15 wherein said first and second core layers are devoid of any appreciable cut-outs.

\* \* \* \* \*

## Exhibit D





US006514367B1

(12) **United States Patent**  
Leighton

(10) Patent No.: **US 6,514,367 B1**  
(45) Date of Patent: **\*Feb. 4, 2003**

(54) **HOT LAMINATION PROCESS FOR THE MANUFACTURE OF A COMBINATION CONTACT/CONTACTLESS SMART CARD**

(76) Inventor: **Keith R. Leighton, 2817 Pulmer Rd., Lorain, OH (US) 44053**

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **09/368,846**

(22) Filed: **Aug. 5, 1999**

#### Related U.S. Application Data

(63) Continuation of application No. 08/918,582, filed on Aug. 19, 1997, now Pat. No. 6,036,099, and a continuation-in-part of application No. 08/727,789, filed on Oct. 7, 1996, now Pat. No. 5,817,207.

(60) Provisional application No. 60/024,255, filed on Aug. 21, 1996, and provisional application No. 60/005,685, filed on Oct. 17, 1995.

(51) Int. Cl.<sup>7</sup> ..... **G06K 19/077**

(52) U.S. Cl. .... **156/153; 156/154; 156/277**

(58) Field of Search ..... **156/277, 153, 156/555, 154; G06K 19/077**

5,250,341 A	10/1993	Kobayashi et al.	
5,268,699 A	12/1993	Laute et al.	
5,272,596 A	12/1993	Honore et al.	
5,396,650 A	3/1995	Terauchi	
5,412,192 A	5/1995	Hoss	
5,438,750 A	8/1995	Venambre	
5,448,110 A	9/1995	Tuttle et al.	
5,519,201 A *	5/1996	Templeton, Jr. et al. ....	235/492
5,567,362 A	10/1996	Grun	
5,719,746 A	2/1998	Ohbuchi et al.	
5,774,339 A	6/1998	Ohbuchi et al.	
5,809,633 A	9/1998	Mundigl et al.	
5,817,207 A *	10/1998	Leighton .....	156/298
6,036,099 A *	3/2000	Leighton .....	235/488
6,248,199 B1	6/2001	Smulson	

#### FOREIGN PATENT DOCUMENTS

GB	2225283	*	5/1990
GB	2279610	*	1/1995
GB	2294899	*	5/1996
JP	6-176214	*	6/1994

\* cited by examiner

Primary Examiner—Jeff H. Aftergut

(74) Attorney, Agent, or Firm—Hahn, Loeser & Parks, LLP

(57) **ABSTRACT**



A plastic smart card, such as a card having a radio frequency identification (RFID) proximity function, including at least one electronic element embedded therein and a physical contact card function and the hot lamination process for the manufacture of this dual function smart card and other

U.S. Patent

Feb. 4, 2003

Sheet 1 of 4

US 6,514,367 B1



U.S. Patent

Feb. 4, 2003

Sheet 2 of 4

US 6,514,367 B1

FIG.-2A




FIG.-3A




FIG.-3B





FIG.-4

U.S. Patent

Feb. 4, 2003

Sheet 3 of 4

US 6,514,367 B1




FIG. - 5A







FIG. - 6

U.S. Patent

Feb. 4, 2003

Sheet 4 of 4

US 6,514,367 B1



US 6,514,367 B1

1

# HOT LAMINATION PROCESS FOR THE MANUFACTURE OF A COMBINATION CONTACT/CONTACTLESS SMART CARD

This application is a continuation of application 08/918, 582, filed Aug. 19, 1997, now U.S. Pat. No. 6,036,099, which claimed the benefit of provisional application Ser. No. 60/024,255, filed Aug. 21, 1996; a continuation-in-part of application Ser. No. 08/727,789 filed Oct. 7, 1996, now U.S. Pat. No. 5,817,207, which claimed the benefit of provisional application Ser. No. 60/005,685, filed on Oct. 17, 1995.

## FIELD OF THE INVENTION

The present invention relates generally to plastic cards and the manufacture thereof by a hot lamination process, and more particularly to smart cards and the manufacture of these such that they conform to industry size and performance standards and conventions and that have a superior outer surface as compared to known smart cards such that the card may receive dye sublimation printing or the like. Even more specifically, the preferred embodiments of the present invention relate to dual function cards containing imbedded electronic elements as well as an exposed electronic contact surface.

## BACKGROUND OF THE INVENTION

As the use of plastic cards for credit cards, automated teller machine (ATM) cards, identification cards, and like continues to become more widespread, the problems associated with the use of such cards correspondingly increase. Credit card fraud and identification card fraud are becoming larger problems everyday, and this fraud has introduced uncertainties into our systems of commerce and our security systems. Using easily available technology, criminals are able to manufacture credit/debit cards, ATM cards, identification cards, and the like having another's account code, identification code, or other personal information embedded in the magnetic stripe thereof. Thus, for example, criminals may steal hundreds or thousands of legitimate credit card account numbers and manufacture many additional cards bearing the stolen information. These fraudulent cards are then usable by the criminals to purchase goods and to receive cash with the legitimate card holder and the card issuer left holding the bill.

Likewise, so called debit cards are becoming increasingly popular. These cards have stored thereon a certain amount of value for which the card owner has previously paid. For example, a subway rider may purchase a card good for X fares, with one fare being deducted from the card each time the owner rides the subway. Criminals have also been able to manipulate the data stored on these cards to defraud the merchants and others.

The ease in which criminals have been able to manufacture and or manipulate known cards results from the existence of the easily altered magnetic stripe storage medium used by known cards. These magnetic stripes are easily programmed and reprogrammed using commonly available technology. Thus, there has been found a need in the plastic card industry to provide a more secure plastic card that is very difficult or impossible to fraudulently manipulate.

The likely successor to magnetic stripe cards is known as a memory or smart card. A smart card can generally be described as a card having an integrated circuit with memory that is capable of making decisions. The category of smart cards can be further divided into subcategories based on the type of memory or type of communication with an associ-

2

ated card reader. Types of smart cards include contact cards (cards requiring physical touch between the terminal reader and the surface of the card) and contactless cards (cards which interact with the terminal reader using an electromagnetic coupling). Contactless cards may also be referred to as "proximity" cards. This technology may serve as a substitute for or be provided as an addition to the magnetic stripe on a card.

One specific type of smart card is a dual function contact/contactless microprocessor chip plastic card commonly referred to in the industry as a dual function card. This card utilizes a single microprocessor to control both physical contact and proximity features of the card.

While these smart cards have been found to have infinitely more capability than magnetic stripe cards as well as being more successful in preventing or limiting fraud, they are more difficult and expensive to manufacture relative to ordinary magnetic stripe cards. One of the biggest obstacles to the wide spread manufacture and use of smart cards has been the inability of card manufacturers to manufacture a smart card that meets all industry standards and specifications, such as those set by the International Standards Organization (ISO), that are sufficiently aesthetically pleasing (wherein the embedded electronics are hidden from view), and that have a sufficiently regular or flat surface such that one or both surfaces of the card may be printed on using the very popular and widespread dye sublimation technology.

Limitations to known plastic cards with embedded computer chips and electronics are that they a) are too thick to work in connection with existing card reading machinery (ATM machines, telephones), b) have a surface that is too irregular to properly and consistently receive dye sublimation printing, c) utilize manufacturing processes making the cards cost prohibitive. Moreover, prior attempts to manufacture a sufficiently thin plastic card including a computer chip embedded therein have resulted in a card with inferior aesthetic qualities such as the ability to see the embedded computer chip through the plastic.

Furthermore, due to the presence of both internal and surface electronics within the card, the manufacture of a dual function card presents its own unique set of obstacles and problems, different from the manufacture of cards with fully embedded electronics.

## SUMMARY OF THE INVENTION

The present invention is therefore directed to a hot lamination method for the manufacture of a plastic card having at least one electronic element embedded therein as well as at least one electronic element with an exposed contact surface and to such plastic cards. The card has an overall thickness in the range of 0.028 inches to 0.032 inches and comprises a plastic core having at least one electronic element embedded therein with at least one of the upper and lower surfaces of the core comprising a coating printed or otherwise applied thereon. A portion of the card's outer surface exposes a contact surface electronic element operatively connected to the card's internal electronics. An overlamine film is preferably provided over the coated surface of the core and the resulting card has a variation in thickness across the surfaces thereof of no greater than approximately 0.0005 inches.

The hot lamination method of the present invention comprises the steps of providing upper (first) and lower (second) plastic core sheets, positioning at least one electronic element between the first and second core sheets to



US 6,514,367 B1

3

thus form a core, and placing the core in a laminator and closing the laminator with minimal or no laminator ram pressure applied to the core. A heat cycle is applied to the core sheets in the laminator to cause complete or partial flow of the plastic sheets. The laminator ram pressure is then increased in combination with the heat. A cooling cycle is then applied to the core in the laminator, preferably with an associated increase in ram pressure, and the core is removed from the laminator.

In the preferred embodiment, the laminated core next undergoes a controlled depth milling operation to expose one or more contact pads which comprise part of the internal, embedded electronic element.

In alternative embodiments, one of the plastic sheets contained a pre-formed window which is positioned over the contact pads, prior to lamination. A spacer, integral to the corresponding platen or separate therefrom, is utilized to prevent or limit the flow of plastic into the window region so as not to coat the contact pads with plastic during the card manufacturing process.

At least one surface of the core is then printed on using a printing press or similar printing apparatus, a sheet of overlamine film is placed on at least one side of the core, and the core is once again placed in a laminator. A heat cycle is applied to the core with its overlamine film, and a cooling cycle is thereafter applied, resulting in a sheet of plastic card stock from which one or more cards may be cut.

Contact surface elements are installed into the window region of a plastic card and in operable contact with contact pads.

The invention is also directed to a card manufactured in accordance with the above process which results in a plastic card having a thickness in the range of approximately 0.028 inches to 0.032 inches with a surface smoothness of at least approximately 0.0005 inches as is required by International Standards Organization (ISO) and American National Standards Institute (ANSI) standards.

The present invention provides numerous advantages over known plastic cards and known plastic card manufacturing processes, and includes the formation of a plastic card with electronic elements such as a computer chip embedded therein with a pleasing aesthetic appearance, having a sufficiently smooth and regular surface such that the card may receive dye sublimation printing, and possessing sufficient durability and characteristics to comply with all industry specifications and standards.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a plastic card in accordance with the present invention;

FIG. 2 is a perspective view of the card shown in FIG. 1, illustrating the embedded and exposed electronics incorporated into the card;

FIG. 2A is a side elevational view of the card core illustrating various electronic elements that may be embedded in a card in accordance with the present invention;

FIG. 3A is a cross sectional view of the card illustrated in FIG. 2, taken through section line 3A—3A.

FIG. 3B is a cross sectional view of the card illustrated in FIG. 2, taken through section line 3B—3B.

FIG. 4 is a perspective view of a plurality of electronic elements positioned on a sheet of plastic core stock and covered by a second sheet of plastic core stock.

FIG. 5 is a schematic cross sectional view illustrating a book comprising the core, containing electronics, as positioned in a laminator;

4

FIG. 5A is an enlarged cross-sectional view of the portion encircled in FIG. 5 for an alternative embodiment, utilizing a spacer, for producing a card according to the present invention;

FIG. 6 schematically illustrates the process of printing on the core;

FIG. 7 is a schematic cross sectional view illustrating the core with overlamine film, as placed in a laminator;

FIG. 8 is an exploded view of a plastic card produced by the process of the present invention.

#### DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to a plastic card including at least one electronic element embedded therein. The present invention also relates to a hot lamination process for the manufacture of plastic cards, and more particularly to a hot lamination process for the manufacturer of plastic cards that include an electronic element, such as a computer chip or other electronic element embedded therein. The electronic element may perform a wide variety of functions and take a wide variety of forms. Such cards, without regard to the particular electronic element embedded therein, will hereinafter be referred to as smart cards. The present invention also relates to a card formed in accordance with the invention.

In its preferred embodiment and as illustrated in FIGS. 1 and 2, the present invention relates to the manufacture of a dual function card, a particular type of smart card which utilizes a dual function contact/contactless microprocessor chip, as described previously herein. However, it will be appreciated by those skilled in the art, that the method of hot lamination described herein could easily be applied to other identity card or smart card applications.

Referring now to FIGS. 1, 2, and 2A there can be seen a plastic card 10 manufactured in accordance with the present invention and including an electronic element, generally 20, embedded therein. Card 10 includes an upper surface 12 and a lower surface 14. Electronic element 20 may take a wide variety of forms (microprocessor chip, circuit board, transponder, etc.) and perform a wide variety of functions. As shown in FIGS. 2, 2A, and 3A, electronic element 20 may comprise a read/write micro-chip 22 including a wire antenna 24 connected thereto, any other suitable electronic element. These electronic elements 20, 22 and 24 and their insertion into plastic cards is not new, however, the present invention provides a new hot lamination process for manufacturing plastic cards 10 with these electronic elements embedded therein such that the cards 10 are of a superior quality, meet all ISO and other industry specifications and standards, and are sufficiently smooth and otherwise is capable of receiving dye sublimation printing. Electronic elements such as these described are available from manufacturers such as Motorola and Philips Electronics.

Upper surface 12 contains a window or cavity 16 formed therein and intended to expose one or more contact pads 26 operatively connected to antenna 24. Upon formation of card 10 in accordance with the preferred embodiment, a microprocessor chip 22 is inserted into window 16 and in electrical connection with contact pads 26. This microprocessor chip may function as a "proximity" or radio frequency identification (RFID) card in conjunction with antenna 24 when electromagnetically used with a compatible terminal reader. Microprocessor chip 22 is also capable of function as a contact card, requiring physical contact between a compatible terminal reader and the surface of chip 22. It should be appreciated that the contact function of the card may be accomplished by any contact sensor whether



US 6,514,367 B1

5

integral to or physically separate from chip 22 and that window 16 may be formed anywhere on surfaces 12 and/or 14 as will accomplish the purposes of the invention.

Specifically, a card in accordance with the present invention has a thickness of approximately in the range of 0.028 inches to 0.032 inches with a surface smoothness of 0.0005 inches. In order to meet the ISO standards for such cards, these tolerances apply to the surface of the microprocessor chip 22 surface as well as to the surface of plastic portion of card 10. It is to be appreciated that cards having a thickness greater than 0.032 inches can easily be manufactured in accordance with the teachings herein while meeting all of the other criteria of the present invention. However, the foreseen product demand is for cards meeting the aforementioned standards.

As shown in FIG. 4, one or more cards 10 in accordance with the present invention may be manufactured by positioning an electronic element 20, including contact points 26, between first and second sheets of card stock 30, 32 to form a core 33. Preferably as shown, a plurality of cards are manufactured simultaneously, and accordingly a plurality of electronic elements 20 are positioned between the first and second sheets of plastic core stock 30, 32. When a plurality of electronic elements 20 are positioned between first and second sheets plastic core stock 30, 32, electronic elements 20 are properly positioned relative to one another such that a plurality cards may be cut from the resulting card stock.

Plastic core sheets 30, 32 may be provided by a wide variety of plastics, the preferred being polyvinyl chloride (PVC) having a thickness in the range of 0.007 inches to 0.024 inches and preferably having a thickness of approximately 0.0125 inches each. Those skilled in the art will recognize that the thickness of the plastic core sheets will depend somewhat upon the thickness of the one or more electronic elements that are to be embedded therebetween if ISO standards are intended to be met. Other suitable plastics that may be utilized include polyester, acrylonitrile-butadiene-styrene (ABS), and any other suitable plastic.

Subsequent to placing one or more electronic elements 20 between the first and second sheets 30, 32 of plastic core stock to form a core 33, this core 33 is placed in a laminator apparatus 40 of the type well known in the art of plastic card manufacturing. As is shown in FIG. 5, laminator 40 includes upper and lower platens 42, 44 for applying ram pressure to an article positioned therebetween. In addition to the ability to apply ram pressure, laminator 40 is preferably of the type having controlled platens 42, 44 that may provide both heat and chill cycles and preferably includes cycle timer to regulate cycle time. Core 33 is positioned between first and second laminating plates 50, 52, one of which is preferably matte finished to provide laminated core 33 with at least one textured outer surface. First and second laminating pads 60, 62 are positioned outside of the laminating plates 50, 52, and first and second steel plates 70, 72 are likewise positioned outside of pads of 60, 62 and the entire assembly forms a book 37 for being positioned in laminator 40 between platens 42, 44.

Once book 37 is positioned in laminator 40 as shown in FIG. 5, the first lamination cycle is initiated by closing laminator platens 42, 44, preferably applying little or no ram pressure to book 37. This is preferably done using hydraulic pressure, and a pressure not to exceed about 10 pounds per square inch is believed sufficient for most applications.

A laminator heat cycle is initiated, bringing the temperature of platens 42, 44 up to a range of 275° F. to 400° F., and most preferably up to a range of 300° F. to 370° F. for a

6

period of ranging between 1 to 20 minutes, but preferably greater than 5 minutes, and most preferably in the range of 7 to 10 minutes for PVC material. It must be understood that the temperatures recited herein are by means of example. The use of thermoplastic material other than PVC or the presence of pigments in the core material may require modification of the heat cycle temperature.

Once the heat cycle has been applied to book 37 as is set forth above, the ram pressure of laminator 40 is increased to facilitate the flow of the plastic core sheets 30, 32 so that the one or more electronic elements 20 become encapsulated thereby, and so that sheets 30, 32 form a uniform core 33 with upper and lower surfaces 34, 35. The ram pressure translates into an effective pressure on core 33 in the range of 200 to 450 psi and preferably in the range of 250 to 350 psi. As can be expected temperature and pressure are inversely related to one another. In other words a lamination cycle at a higher temperature will require less pressure to be applied to core 33, and conversely a lower temperature heat cycle will require increased ram pressure. Damage to the electronic components can result from excessive ram pressure on the core while insufficient ram pressure will likely cause an inadequate flow of the plastic resulting in air pockets or an irregular card surface.

As mentioned, the use of matte finished laminator plates 50, 52 provides surfaces 34, 37 with a slightly roughened or textured quality which will facilitate the application of a coating thereto as is discussed below. The ram pressure applied during the heat cycle and the length of the heat cycle may vary, depending especially upon the size of sheets 30, 32. For example, the cycle time may be in the range of 10-15 minutes. In one example, at a temperature of approximately 320 degrees Fahrenheit, a ram pressure of 940.135 pounds per square inch (p.s.i.), producing a pressure of about 275 psi at the core 33 surface, was applied for 10-15 minutes to form a uniform core 33, using sheets 30, 32 of a size in the range of 12 inches by 24 inches to 24 inches by 36 inches.

Subsequent to the above heat cycle, laminator 40 applies a chill cycle to book 35 during which time the ram pressure of the laminator 40 is increased, preferably by approximately 10-40% and most preferably about 25% until the platens 42, 44 have cooled so as to return the core material to a solid state. In the preferred method the platens 42, 44 are cooled to approximately 40° F. to 65° F. for approximately 10-15 minutes. Core 33 may then be removed from laminator 40 for additional processing.

Subsequent to the removal of core 33 from laminator 40, and as illustrated in FIG. 6, core 33 is coated on at least one of its upper and lower surfaces 34, 35 with a layer of printing ink 36. This may be accomplished using a wide variety of printing techniques such as offset printing, letterpress printing, screen printing, roller coating, spray printing, litho-printing, and other suitable printing techniques. As shown in FIG. 6, core 33 is fed in the direction indicated with arrow A through a printing press, a lithographic printer, or a similar apparatus 80. This printing step is performed to coat at least one surface 34, 35 of core 33 with a layer of aesthetically pleasing ink 36. This layer of ink 36 can also serve to cosmetically hide the one or more electronic elements 20 that are embedded within core 33, and prevent these one or more electronic elements 20 from showing through the relatively thin core 33. In this manner, the one or more electronic elements 20 encapsulated in core 33 are completely hidden from view without requiring the plastic used in the manufacture core 33 to be excessively thick (exceeding ISO standards for cards of this type).

Referring now to FIG. 7, the final preferred, but optional processing of core 33, which now comprises a layer of ink

US 6,514,367 B1

7

36 or the like on at least one surface 34, 35 thereof, is schematically illustrated. An overlamine layer such as clear overlamine film 38 is positioned on at least one ink coated surface 34, 35 of core 33, and preferably core 33 is positioned between two similar sheets of overlamine film 38, 39 as shown. Overlamine film is very thin, for example in the range of 0.0015" thick. A book 135 is then constructed for insertion into laminator 40 as is schematically illustrated in FIG. 7. Book 135 comprising core 33, including at least one layer of ink 36 and at least one layer of overlamine film 38, 39 is positioned between laminating plates which are preferably highly polished plates such as mirror finished stainless steel plates 91, 92. Book 135 also comprises first and second laminating pads 60, 62 and first and second steel plates 70, 72 as is discussed above in relation to FIG. 7.

When book 135 is positioned between upper and lower platens 42, 44 of laminator 40 as shown in FIG. 7, the laminator is closed and a heat cycle in the range of 175° F. to 300° F., and most preferably in the range of 180° F. to 275° F., is applied to book 135 for a period of 10 to 25 minutes to produce a pressure on book 135 of between 200 to 450 psi, preferably 250-350 psi, with a ram pressure that varies depending upon sheet size or the ram size of the laminator 40, but which is typically approximately 1000 p.s.i. with an 18 inch diameter ram. This step causes the overlamine layer 38 to flow in order to produce a uniform protective layer over the printing.

The laminator 40 is then caused to execute a chill cycle, preferably with a corresponding increase in ram pressure. For example, the chill temperature may be in the range of 40° F. to 65° F. and last for a period of 10 to 25 minutes. However, any combination of temperature and time which permits the re-solidification of the overlamine layer 38 may be used. A ram pressure increase of approximately 10 to 40% over the pressure used for the heat cycle has been found to be preferable, with a pressure increase of approximately 25% being most desirable.

It is important to note that the use of pressure, or more significantly temperature, in the second lamination cycle should only affect the overlamine layer 38 and should not cause softening or re-flow of plastic core 33. In lieu of this preferred overlamination process, it is to be understood that colorfast inks may not require an overlamine layer or that alternative overlaminates such as those applied by spray, silk screening or roll on may be used.

Subsequent to the above described second lamination cycle, a sheet of plastic card stock is provided which comprises at least core 33 with at least one surface 34, 35 thereof covered by a layer of ink 36, and with at least one surface 34, 35 thereof covered by a layer of overlamine film 38, 39.

Preferably plastic card stock manufactured in accordance with the present invention comprises core 33 covered on both surfaces 34, 35 with a layer of ink 36 which is positioned between layers of overlamine film 38, 39, all of which has been laminated together as described and as shown in FIG. 8. One or more cards 10 then may be cut from the resulting plastic card stock and card 10 will have a thickness in the range of 0.028 inches to 0.032 inches with variation in overall thickness across the surfaces 12, 14 thereof being no greater than approximately 0.0005 inches. The one or more cards 10 can thus be said to have a glossy surface smoothness of approximately 0.0005 inches or better. Thus, a card 10 manufactured in accordance with the present invention includes at least one surface 12, 14 at preferably both surfaces 12, 14 that are sufficiently smooth, glossy and regular to receive dye sublimation printing.

8

In the preferred embodiment, each card 10 undergoes a controlled-depth milling operation to form a window or cavity 16 and to expose one or more of the contact pads 26 connected to the antenna 24. Thereafter, a microprocessor chip 22 having a contact surface is inserted into the cavity and in electronic contact with contact pads 26. Chip 22 may be attached to contact pads 26 by known means such as conductive adhesives (including those cured by UV or sonic energy) or low temperature solder. The overall thickness of the card including the area occupied by chip 22 meets ISO standards and is capable of operation in compatible physical readers.

In an alternative embodiment, a cavity or window 16 is formed in the first or second sheet of plastic core stock, prior to the first lamination step. The core stock is positioned over the electronic element, generally 20, to expose one or more contact pads 26. This may also be done using electronic elements wherein microprocessor chip 22 is already attached to contact pads 26 and/or antenna 24 in which case the cavity is positioned over and around chip 22. As shown in FIG. 5a, a spacer 90 is inserted into cavity 16 and over contact pads 26 or chip 22. The spacer 90 may be integral to one of the matte laminating plates 50, 52 or separate therefrom and made of any suitable non-stick material such as Teflon®. Spacer 90 is utilized to prevent or limit the flow of plastic into cavity 16 during the lamination process so as not to cover contact pads 26 or chip 22 with plastic. When spacer 90 is non-integral with matte laminating plate 50 or 52 it may be removed or cut-away after either the lamination or overlamination process to expose cavity 16 and allow microchip 22 to be inserted therein and retained by such means as are known in the art, including solder or adhesives. In this embodiment where the chip is installed prior to lamination, when viewed in cross-section the outer surface of chip 22 is below the upper surface 34 or core sheet 35 prior to lamination, thus core sheets will accept the majority of applied pressure from the laminator. Spacer 90 provides further protection. As the core material softens, the plastic will flow around spacer 90 and chip 22 and the distance between the outer surface of chip 22 and the upper surface of core sheet 35 will decrease.

Those skilled in the art will recognize that the foregoing description has set forth the preferred embodiment of the invention in particular detail and it must be understood that numerous modifications, substitutions, and changes may be undertaken without departing from the true spirit and scope of the present invention as defined by the ensuing claims. For example, it should be understood that the methods as described can be performed with or without the printing or coating steps and still fall within the scope of the invention.

What is claimed is:

1. A process for incorporating at least one electronic element in the manufacture of a plastic card, comprising the steps of:

- (a) providing first and second plastic core sheets;
- (b) positioning said at least one electronic element in the absence of a non-electronic carrier directly between said first and second plastic core sheets to form a core, said plastic core sheets defining a pair of inner and outer surfaces of said core;
- (c) positioning said core in a laminator apparatus, and subjecting said core to a heat and pressure cycle, said heat and pressure cycle comprising the steps of:
  - (i) heating said core for a first period of time;
  - (ii) applying a first pressure to said core for a second period of time such that said at least one electronic element is encapsulated by said core;

US 6,514,367 B1

9

(iii) cooling said core while applying a second pressure to said core, the second pressure being at least 10% greater than the first pressure; and

(d) milling a region of said core to a controlled depth so as to form a cavity which exposes at least one contact pad of said at least one electronic element.

2. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said laminator apparatus has first and second laminating plates, at least one of said first and second laminating plates having a matte finish for creating a textured surface on at least one of said outer surfaces of said core.

3. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 2, wherein each of said first and second laminating plates has a matte finish for creating said textured surface on both of said outer surfaces of said core.

4. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said first and second plastic core sheets are made from a material selected from the group consisting of polyvinyl chloride, polyester, and acrylonitrile-butadiene-styrene, each of said sheets having a thickness in the range of 0.007 to 0.024 inch.

5. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 4, wherein said first and second plastic core sheets have a thickness of approximately 0.0125 inch.

6. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said second pressure ranges from about 10% to about 40% greater than said first pressure.

7. A process as recited in claim 1 having a further step following step (c), said step comprising: positioning a layer of overlamine film on at least one of said surfaces of said core, positioning said overlamine film and said core in a laminator apparatus and laminating said layer of overlamine film to said core in said laminator to thereby form a sheet of plastic card stock.

8. The process of claim 7, further comprising the step of coating said at least one surface of said core with a layer of ink prior to positioning said overlamine film on said at least one surface of said core.

9. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said core is heated in step (c)(i) to a temperature in the range of 275° F. to 400° F. and said first period of time is at least five (5) minutes.

10. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said first pressure is approximately 450 p.s.i. and said second period of time is at least 10 minutes.

11. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein a coating step is carried out on at least one surface of said core utilizing a printing press.

12. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein a coating step is carried out on at least one surface of said core utilizing a coating technique selected from the group consisting of silk screen printing, offset printing, letterpress printing, screen printing, roller coating, spray printing, and litho-printing.

13. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, having a further step after said step (c) comprising:

10

(a) positioning an overlamine film on said at least one surface of said core;

(b) subjecting said core to a heat and pressure cycle comprising the steps of:

(i) heating said core to a temperature between approximately 175° F. to 300° F. for approximately 10 to 25 minutes;

(ii) applying approximately 1000 p.s.i. pressure to said core; and

(iii) cooling said core to a temperature in the range of approximately 40° F. to 65° F. for approximately 10 to 25 minutes.

14. The process of claim 13, further comprising the step of coating said at least one surface of said core with a layer of ink prior to positioning said overlamine film on said at least one surface of said core.

15. A process as recited in claim 1 comprising the further step of inserting a second electronic element into said cavity, the second electronic element being in electrical communication with the at least one electronic element.

16. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said at least one electronic element is a micro-chip and an associated circuit board antenna or an associated wire antenna.

17. The process for incorporating at least one electronic element in the manufacture of a plastic card as recited in claim 1, wherein said at least one electronic element is a read/write integrated chip and an associated antenna.

18. The process according to claim 1, wherein the pressure on said core in step (c)(i) is less than 10 p.s.i.

19. The process according to claim 1, wherein said core is heated in step (c)(ii).

20. A process for incorporating at least one electronic element in the manufacture of a plastic card, comprising the steps of:

(a) providing first and second plastic core sheets;

(b) positioning said at least one electronic element in the absence of a non-electronic carrier directly between said first and second plastic core sheets to form a core, said plastic core sheets defining a pair of inner and outer surfaces of said core;

(c) positioning said core in a laminator apparatus, and subjecting said core to a heat and pressure cycle, said heat and pressure cycle comprising the steps of:

(i) heating said core for a first period of time;

(ii) applying a first pressure to said core for a second period of time such that said at least one electronic element is encapsulated by said core;

(iii) cooling said core while applying a second pressure to said core, the second pressure being at least 10% greater than the first pressure.

21. The process according to claims 20, further comprising:

forming a cavity in said core.

22. The process according to claim 21, wherein the step of forming a cavity in said core comprises:

after step (c), milling a region of said core to a controlled depth so as to form a cavity which exposes at least one contact pad of said at least one electronic element.

23. The process according to claim 22, further comprising:

inserting a second electronic element into said cavity, the second electronic element being in electrical communication with the at least one electronic element.

\* \* \* \* \*